# Cumberland PRODUCTS INCORPORATED

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Activator

Other means of identification

Product code CP-5802 (all sizes)

Recommended use Activator
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

Address

Cumberland Products Inc.

50 Commerce Parkway

Hodgenville, KY 42748

United States

**Telephone** TECH SUPPORT 800-223-1918 Mick or Dan

SALES 800-223-1918 PHONE 800-223-1918

Websitewww.cumberlandproductsinc.comE-mailpo@cumberlandproductsinc.com

Contact person Wayne Moore, Bruce Barlow, John Moore

Emergency phone number EMERGENCY 24 Hrs. ChemTrec 800-424-9300

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsAcute toxicity, oralCategory 4

Acute toxicity, dermal Category 4 Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Sensitization, respiratory Category 1 Sensitization, skin Category 1 Carcinogenicity Category 2 Reproductive toxicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 1

Category 2

Specific target organ toxicity, repeated

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

#### **Hazard statement**

Flammable liquid and vapor. Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

# Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

#### Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

#### Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

# Disposal

 $\label{local/regional/national/international regulations.} Dispose of contents/container in accordance with local/regional/national/international regulations.$ 

Hazard(s) not otherwise classified (HNOC)

None known.

# Supplemental information

42.83% of the mixture consists of component(s) of unknown acute oral toxicity. 60.15% of the mixture consists of component(s) of unknown acute dermal toxicity. 23.74% of the mixture consists of component(s) of unknown acute inhalation toxicity. 68.4% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 52.83% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Hexamethylene Diisocyanate		28182-81-2	30 - < 50
Trimethyl Benzene		25551-13-7	5 - < 20
Trimetyl Benzene		95-63-6	5 - < 20
Xylene		1330-20-7	5 - < 20
2-Butoxyethylacetate		112-07-2	5 - < 15
Glycol Ether PM Acetate		108-65-6	5 - < 15
Butyl Cellosolve/Glycol Ether EB		111-76-2	0< 5
Ethylbenzene		100-41-4	0 - < 5
Isopropyl Benzene		98-82-8	0 - < 5
Other components below reportable levels	8		< 1

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER

or doctor/physician.

**Skin contact**Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical

advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Material name: Activator

CP-5802 (all sizes) Version #: 01 Issue date: 07-27-2015 2 / 13

#### Eye contact

Ingestion

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods
General fire hazards

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

ergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

#### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

#### 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Components	Туре	Value	
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Isopropyl Benzene (CAS 98-82-8)	PEL	245 mg/m3	
		50 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
<b>US. ACGIH Threshold Limit Value</b>	s		
Components	Туре	Value	
2-Butoxyethylacetate (CAS 112-07-2)	TWA	20 ppm	
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	TWA	20 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Isopropyl Benzene (CAS 98-82-8)	TWA	50 ppm	
Trimethyl Benzene (CAS 25551-13-7)	TWA	25 ppm	
Trimetyl Benzene (CAS 95-63-6)	TWA	25 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
2-Butoxyethylacetate (CAS 112-07-2)	TWA	33 mg/m3	
		5 ppm	
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3	
		100 ppm	

Components	Туре	Value	
Isopropyl Benzene (CAS 98-82-8)	TWA	245 mg/m3	
,		50 ppm	
Trimetyl Benzene (CAS 95-63-6)	TWA	125 mg/m3	
,		25 ppm	
US. Workplace Environmental Ex	kposure Level (WEEL) Guides		
Components	Type	Value	
Glycol Ether PM Acetate (CAS 108-65-6)	TWA	50 ppm	

## **Biological limit values**

<b>ACGIH Biological</b>	<b>Exposure Indices</b>
-------------------------	-------------------------

Components	Value	Determinant	Specimen	Sampling Time
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

#### US - California OELs: Skin designation

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Glycol Ether PM Acetate (CAS 108-65-6)

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2) Skin designation applies. Isopropyl Benzene (CAS 98-82-8) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Can be absorbed through the skin.

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

# Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Liquid.
Color Colorless
Odor Solvent.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -82.3 °F (-63.5 °C) estimated Initial boiling point and boiling 336 °F (168.89 °C) estimated

range

Flash point 112.0 °F (44.4 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 4.29 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 645 °F (340.56 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density0.88 g/cm3 estimatedFlammability classCombustible II estimatedPercent volatile62.5 w/w % By Weight65.83 v/v % By Volume

Specific gravity 0.88 estimated

VOC (Weight %)

5.03 lb/gal (Regulatory VOC - Less Water Less Exempts)

5.03 lb/gal (Actual VOC - With Water Less Exempts)

602.31 g/L (Regulatory VOC - Less Water Less Exempts) 602.31 g/L (Actual VOC - With Water With Exempts)

#### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

riazardodo porymenzation does not occur.

**Conditions to avoid**Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

 Material name: Activator
 SDS US

 CP-5802 (all sizes)
 Version #: 01
 Issue date: 07-27-2015
 6 / 13

Incompatible materials
Hazardous decomposition
products

Strong acids. Strong oxidizing agents. Halogens. No hazardous decomposition products are known.

#### 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by

inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin contact** Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. May cause an allergic skin

reaction. May cause respiratory irritation.

Components **Species Test Results** 2-Butoxyethylacetate (CAS 112-07-2) **Acute Dermal** LD50 Rabbit 1500 mg/kg Oral Rat LD50 2400 mg/kg Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2) Acute Dermal LD50 Rabbit 400 mg/kg Inhalation LC50 Mouse 700 ppm, 7 Hours Rat 450 ppm, 4 Hours Oral LD50 Guinea pig 1.2 g/kg Mouse 1.2 g/kg Rabbit 0.32 g/kg Rat 560 mg/kg Ethylbenzene (CAS 100-41-4) **Acute Dermal** LD50 Rabbit 17800 mg/kg Oral LD50 Rat 3500 mg/kg Isopropyl Benzene (CAS 98-82-8) **Acute** Inhalation LC50 Mouse 2000 ppm, 7 Hours 24.7 mg/l, 2 Hours 8000 ppm, 4 Hours Rat Oral LD50 Rat 1400 mg/kg

Material name: Activator SDS US

CP-5802 (all sizes) Version #: 01 Issue date: 07-27-2015

**Test Results** Components **Species** 

Trimethyl Benzene (CAS 25551-13-7)

**Acute** 

Oral

LD50 Rat 8970 mg/kg

Trimetyl Benzene (CAS 95-63-6)

**Acute** Dermal

LD50 Rabbit > 3160 mg/kg

Inhalation

LC50 Rat > 2000 ppm, 48 Hours

Oral

Rat LD50 6 g/kg

Xylene (CAS 1330-20-7)

Acute

**Dermal** 

LD50 Rabbit > 43 g/kg

Inhalation

LC50 Mouse 3907 mg/l, 6 Hours Rat 6350 mg/l, 4 Hours

Oral

LD50 Mouse 1590 mg/kg

> Rat 3523 - 8600 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

Ethylbenzene (CAS 100-41-4) 2B Possibly carcinogenic to humans. Isopropyl Benzene (CAS 98-82-8) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans. Xylene (CAS 1330-20-7)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Components in this product have been shown to cause birth defects and reproductive disorders in Reproductive toxicity

laboratory animals. Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Not an aspiration hazard. Aspiration hazard

**Chronic effects** Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Components Species Test Results

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Aquatic

Fish LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

Ethylbenzene (CAS 100-41-4)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours

Isopropyl Benzene (CAS 98-82-8)

Aquatic

Crustacea EC50 Brine shrimp (Artemia sp.) 3.55 - 11.29 mg/l, 48 hours

Fish LC50 Rainbow trout, donaldson trout 2.7 mg/l, 96 hours

(Oncorhynchus mykiss)

Trimetyl Benzene (CAS 95-63-6)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours

Xylene (CAS 1330-20-7)

**Aquatic** 

Fish LC50 Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butyl Cellosolve/Glycol Ether EB0.83Ethylbenzene3.15Isopropyl Benzene3.66Xylene3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

#### 14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number UN1263

UN proper shipping name Paint related material including paint thinning, drying, removing, or reducing compound, MARINE

**POLLUTANT** 

Transport hazard class(es)

Class 3 Subsidiary risk -

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

3 Label(s) Packing group Ш

**Environmental hazards** 

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 149, B52, IB2, T4, TP1, TP8, TP28

Packaging exceptions 150 173 Packaging non bulk 242 Packaging bulk

**IATA** 

UN1263 **UN** number

**UN** proper shipping name Paint related material (including paint thinning or reducing compounds)

Transport hazard class(es)

Class 3 Subsidiary risk П Packing group **Environmental hazards** No. 3L **ERG Code** 

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Not established.

Cargo aircraft only Allowed.

**IMDG** 

**UN** number UN1263

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid UN proper shipping name

lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

Class 3 Subsidiary risk Packing group П **Environmental hazards** 

Marine pollutant Yes F-E, S-E **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



#### Marine pollutant



General information DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

2-Butoxyethylacetate (CAS 112-07-2)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Xylene (CAS 1330-20-7)

Listed.

Listed.

Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

#### SARA 313 (TRI reporting)

CAS number	% by wt.	
95-63-6	5 - < 20	
1330-20-7	5 - < 20	
112-07-2	5 - < 15	
111-76-2	0< 5	
100-41-4	0 - < 5	
98-82-8	0 - < 5	
	95-63-6 1330-20-7 112-07-2 111-76-2 100-41-4	95-63-6 5 - < 20 1330-20-7 5 - < 20 112-07-2 5 - < 15 111-76-2 0< 5 100-41-4 0 - < 5

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Butoxyethylacetate (CAS 112-07-2)

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Xylene (CAS 1330-20-7)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Material name: Activator SDS US

11 / 13

CP-5802 (all sizes) Version #: 01 Issue date: 07-27-2015

#### **US** state regulations

## US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

2-Butoxyethylacetate (CAS 112-07-2)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Ethylbenzene (CAS 100-41-4) Isopropyl Benzene (CAS 98-82-8) Trimethyl Benzene (CAS 25551-13-7) Trimetyl Benzene (CAS 95-63-6)

Xylene (CAS 1330-20-7)

#### **US. Massachusetts RTK - Substance List**

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Ethylbenzene (CAS 100-41-4) Isopropyl Benzene (CAS 98-82-8) Trimethyl Benzene (CAS 25551-13-7) Trimetyl Benzene (CAS 95-63-6) Xylene (CAS 1330-20-7)

#### US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethylacetate (CAS 112-07-2)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Ethylbenzene (CAS 100-41-4) Isopropyl Benzene (CAS 98-82-8) Trimethyl Benzene (CAS 25551-13-7) Trimetyl Benzene (CAS 95-63-6) Xylene (CAS 1330-20-7)

#### US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethylacetate (CAS 112-07-2)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Ethylbenzene (CAS 100-41-4) Isopropyl Benzene (CAS 98-82-8) Trimethyl Benzene (CAS 25551-13-7) Trimetyl Benzene (CAS 95-63-6)

Xylene (CAS 1330-20-7)

#### **US. Rhode Island RTK**

2-Butoxyethylacetate (CAS 112-07-2)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Ethylbenzene (CAS 100-41-4) Isopropyl Benzene (CAS 98-82-8) Trimetyl Benzene (CAS 95-63-6) Xylene (CAS 1330-20-7)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 Isopropyl Benzene (CAS 98-82-8) Listed: April 6, 2010

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

Country(s) or region Inventory name On inventory (yes/no)\*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 07-27-2015

Version # 01

**Disclaimer** Cumberland Products Inc. cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Material name: Activator sps us