

New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

MSDS Preparation Date (mm/dd/yyyy): 02/01/2013

Page 1 of 7

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

Product Code(s) :

Product Use : Hydraulic/transmission fluid

Chemical Family : Mixture.

Supplier's name and address: Manufacturer's name and address:

Viscosity Oil Company Refer to Supplier

600-H Joliet Road Willowbrook, IL, U.S.A.

60527

Information Telephone # : (630) 850-4000

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887

(Outside U.S.).

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is not a WHMIS controlled product in Canada.

OSHA: This material is not classified as hazardous under OSHA regulations (29

CFR Part 1910.1200).

Emergency Overview: Dark brown liquid. Petroleum odor.

Fumes from heated product or mists may irritate respiratory tract. May cause eye and

skin irritation. Toxic fumes are released in fire situation.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation: Fumes from heated product or mists, may irritate respiratory tract.

Skin : May cause mild skin irritation. Oils can block the skin pores causing an acne-like disorder.

Hydrocarbons injected into the skin under pressure can cause severe injury. Symptoms from pressure injection may include inflammation, swelling and severe, permanent tissue damage. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Exposure to hot material may cause thermal burns.

Eyes : May cause mild eye irritation.

Ingestion : May have laxative effects. May cause nausea, vomiting, and diarrhea.

Effects of long-term (chronic) exposure

: Prolonged or repeated skin contact may cause irritation, defatting or dermatitis (rash). Oils can block the skin pores causing an acne-like disorder. Overexposure to sprays or mists may cause chemical pneumonitis (inflammation of lung tissue).

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS



New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

MSDS Preparation Date (mm/dd/yyyy): 02/01/2013

Page 2 of 7

<u>Ingredients</u>	CAS#	Wt.%
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	1.00 - 5.00
Hydrotreated heavy paraffinic distillate	64742-54-7	60.00 - 100.00
Paraffinic hydrocarbons	72623-86-0	0.50 - 1.50

SECTION 4 - FIRST AID MEASURES

Inhalation

: If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. When symptoms persist or in all cases of doubt seek medical advice.

Skin contact

Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Wash contaminated clothing before reuse. When symptoms persist or in all cases of doubt seek medical advice. If thermal burns are present: Treat all thermal burns with appropriate first aid measures for degree of burn. Cool skin rapidly with cold water, if material is hot. Subcutaneous injection may require surgical treatment. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Eye contact

In the case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.

Notes For Physician : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Vapours are heavier than air and collect in confined and low-lying areas. Material will float on water and can be re-ignited at the water's surface.

Flammability classification (OSHA 29 CFR 1910.1200)

Non-flammable.

Oxidizing properties : None known.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Suitable extinguishing media : Dry chemical; Carbon dioxide (CO2); Foam; water fog. Do not use a solid water stream as it may scatter and spread fire.

Silean as it may scatter and s


Special fire-fighting procedures/equipment

: Move containers from fire area if safe to do so. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Water spray may be useful in cooling equipment exposed to heat and flame. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products

 Carbon oxides; Hydrocarbons; Phosphorus compounds; nitrogen oxides (NOx); Sulphur oxides.

NFPA Rating <u>0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe</u>





New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

MSDS Preparation Date (mm/dd/yyyy): 02/01/2013

Page 3 of 7

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions

: Wear suitable protective equipment. Refer to protective measures listed in sections 7 and 8. Keep people away from and upwind of spill/leak.

Environmental precautions

Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Spill response/cleanup

Ventilate area of release. Remove all sources of ignition. Stop spill or leak at source if safely possible. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Do not flush into surface water or sanitary sewer system. Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Prohibited materials

None known or reported by the manufacturer.

Special spill response procedures

If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).

US CERCLA Reportable quantity (RQ): None reported.

SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures

: Do not breathe fumes or mists. Use only in well-ventilated areas. Wear protective gloves/clothing and eye/face protection. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Keep away from incompatibles. Keep container tightly closed. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Wash thoroughly after handling.

Storage requirements

Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Inspect periodically for damage or leaks. Protect against physical damage. No smoking in the area. Keep away from incompatibles.

Incompatible materials

: Oxidizing agents.

Special packaging materials

: Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits					
	ACGIH TLV		OSHA PEL		
<u>Ingredients</u>	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>	
Distillates (petroleum), solvent-refined heavy paraffinic	5 mg/m³ (As 'Oil mist, mineral')	10 mg/m³ (As 'Oil mist, mineral')	5 mg/m³ (As 'Oil mist, mineral')	N/Av	
Hydrotreated heavy paraffinic distillate	5 mg/m³ (As 'Oil mist, mineral')	10 mg/m³ (As 'Oil mist, mineral')	5 mg/m³ (As 'Oil mist, mineral')	N/Av	
Paraffinic hydrocarbons	N/Av	N/Av	N/Av	N/Av	

Ventilation and engineering measures


: Use only in well-ventilated areas. Provide sufficient ventilation to keep vapour concentration below the given TLV and/or PEL.

Respiratory protection

: Respiratory protection is required if the concentrations exceed the TLV. Use NIOSH/MSHA approved equipment. Advice should be sought from respiratory protection specialists.

Skin protection

: Wear protective gloves. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.). Advice should be sought from glove suppliers.





New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

MSDS Preparation Date (mm/dd/yyyy): 02/01/2013

Page 4 of 7

: Safety goggles or glasses as appropriate for the job. Eye / face protection

: Where extensive exposure to product is possible, use resistant coveralls, apron and Other protective equipment

> boots to prevent contact. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.). Ensure that eyewash stations and safety showers are

close to the workstation location.

General hygiene considerations

Do not breathe fumes or mists. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Remove and wash contaminated clothing before re-use.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

: Dark brown liquid. Physical state Liquid. **Appearance**

Petroleum odour. : N/Av **Odour threshold** Odour

N/Ap рΗ

N/Av : 0.875 **Boiling point** Specific gravity

- 40°C (- 40°F) Melting/Freezing point Coefficient of water/oil distribution

: N/Av

Vapour pressure (mmHg @ 20° C / 68° F) Solubility in water : <1%

: N/Av

N/Av Vapour density (Air = 1) Evaporation rate (n-Butyl acetate = 1)

: N/Av

Volatile organic Compounds (VOC's) Volatiles (% by weight) : N/Av

N/Av

>200°C (>392°F) Flash point

Cleveland Open Cup · N/Av Flash point Method Auto-ignition temperature

Lower flammable limit (% by vol.) Upper flammable limit (% by vol.)

N/Av · N/Av

N/Ap : N/Ap Flame Projection Length Flashback observed

60 cSt at 40°C (104°F) Viscosity

Absolute pressure of container

: N/Ap

Section 10: Stability And Reactivity

Stable under normal conditions. Stability and reactivity

Hazardous polymerization Hazardous polymerisation does not occur.

Direct sources of heat. Avoid contact with incompatible materials. Conditions to avoid

Materials To Avoid And Incompatibility

Oxidizing agents.

Hazardous decomposition products

None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

: Eyes, skin, respiratory system and digestive system. Target organs

Routes of exposure : Inhalation: YES Skin Absorption: NO Skin & Eyes: YES Ingestion: YES

Toxicological data : There is no available data for the product itself, only for the ingredients. See

below for individual ingredient acute toxicity data.

	LC50(4hr)	LD50	
<u>Ingredients</u>	inh, rat	(Oral, rat)	(Rabbit, dermal)



New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

MSDS Preparation Date (mm/dd/yyyy): 02/01/2013

Page 5 of 7

Distillates (petroleum),	N/Av	> 5000 mg/kg	> 5000 mg/kg
solvent-refined heavy			
paraffinic			
Hydrotreated heavy	N/Av	>15000 mg/kg	>5000 mg/kg
paraffinic distillate			
Paraffinic hydrocarbons	>2180 mg/m³	>5000 mg/kg	>2000 mg/kg

No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP. Carcinogenic status

Not expected to be cause reproductive effects. Reproductive effects

Teratogenicity Not expected to be a teratogen.

Mutagenicity Not expected to be mutagenic in humans.

Epidemiology No information available.

Not expected to be a skin or respiratory sensitizer. Sensitization to material

No information available. Synergistic materials

May be mildly irritating to eyes and skin. Irritancy

None known. other important hazards

Conditions aggravated by overexposure

: Pre-existing skin and respiratory disorders.

SECTION 12 - ECOLOGICAL INFORMATION

No data is available on the product itself. The product should not be allowed to enter **Ecotoxicity**

drains or water courses, or be deposited where it can affect ground or surface

waters.

The product itself has not been tested. Mobility

Persistence The product itself has not been tested. None of the ingredients in this product are

considered to be readily biodegradable, and this product is not soluble in water.

Therefore, this product is expected to persist in the environment.

: The product itself has not been tested. **Bioaccumulation potential**

Other Adverse Environmental effects

: None known.

SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice. Refer to

> protective measures listed in sections 7 and 8. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or

near this container.

Dispose in accordance with all applicable federal, state, provincial and local Methods of Disposal

regulations. Contact your local, state, provincial or federal environmental agency for

specific rules.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the

criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state

and federal environmental agencies.

SECTION 14: TRANPORT INFORMATION					
Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
49CFR/DOT	None	Not regulated.	Not regulated	none	\otimes



Viscosity Oil Company 600-H Joliet Road Willowbrook, IL, U.S.A., 60527

Telephone: 001-630-850-4000

New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

MSDS Preparation Date (mm/dd/yyyy): 02/01/2013

Page 6 of 7

49CFR/DOT Additional information	None.				
TDG	None	Not regulated.	Not regulated	none	\otimes
TDG Additional information	None.				

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: None reported. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

International Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.

SECTION 16 - OTHER INFORMATION

HMIS Rating : *- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: 1 Flammability: 1 Reactivity: 0

Legend : ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability

Act of 1980


CFR: Code of Federal Regulations

cSt: Centistokes

DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer IMDG: International Maritime Dangerous Goods





New Holland AmbrA Mastertran Ultraction, Ultraction (FF)

MSDS Preparation Date (mm/dd/yyyy): 02/01/2013

Page 7 of 7

Inh: Inhalation

LC: Lethal Concentration

LD: Lethal Dose

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2012.

2. International Agency for Research on Cancer Monographs, searched 2012.

3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases

(Chempendium, HSDB and RTECs). - 2012. 4. US EPA Title III List of Lists - July 2011. 5. California Proposition 65 List - 22 June 2012.

Prepared for:

References

Viscosity Oil Company

600-H Joliet Road, Willowbrook, IL, U.S.A., 60527

Telephone: 001-630-850-4000 http://www.viscosityoil.com

Please direct all enquiries to Viscosity Oil.



Prepared by:

ICC The Compliance Center Inc.

http://www.thecompliancecenter.com



DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Viscosity Oil Company and CCOHS' Web Information Service. The information in the Material Safety Data Sheet (MSDS) is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Viscosity Oil Company expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Viscosity Oil Company.

Preparation Date (mm/dd/yyyy)

: 02/01/2013

END OF DOCUMENT