SAFETY DATA SHEET

Issue Date 13-Dec-2012 Revision Date 11-Jun-2015 Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name ACE Silicone Sealant – White & Colors

Product Code 18407, 11961, 11959, 11960, 11315, 1213222, 1213214

Other means of Identification

SDS# RD-0081

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Silicone Sealant.

Details of the Supplier of the Safety Data Sheet

Supplier Address

ACE Hardware Corp. 2200 Kensington Ct Oak Brook, IL 60523

Emergency Telephone Number

Company Phone Number 630-990-6600

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation Category 2

Signal Word Warning

Hazard Statements

Causes skin irritation



Appearance Clear/opaque orcolored paste

Physical State Paste

Odor Acetic Acid Odor (Vinegarodor)

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap andwater If skin irritation persist: Get medicaladvice/attention Take off contaminated clothing and wash before reuse

Hazards Not Otherwise Classified(HNOC)

Not Applicable

Other Information

Not Applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CASNo	Weight-%
Hydroxy-terminated Dimethylsiloxane	70131-67-8	>50
Non-hazardous ingredients*	Proprietary	>10
Amorphous silica (glass)	7631-86-9	<13
Polydimethylsiloxane	63148-62-9	<10
Methyltriacetoxysilane	4253-34-3	<6
Titanium Dioxide	13463-67-7	<5
Ethyltriacetoxysilane	17689-77-9	<6

^{*} Unlisted ingredients are not considered hazardous under the OSHA GHS Hazard Communication Standard (29 CFR 1910.1200). (Methyltriacetoxysilane) Observe limits for acetic acid formed during curing on exposure to water or humid air. (Silica, amorphous; Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state

4. FIRST AID MEASURES

First Aid Measures

General advice Provide this SDS to medical personnel fortreatment.

If symptoms are experienced remove source of contamination or move victim to fresh air. If

irritation persists, obtain medicaladvice.

Eye Contact Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5

minutes while holding the eyelid(s) open. Obtain medical attention.

Ingestion Rinse mouth thoroughly with water. If irritation or discomfort occurs, obtain medical advice.

Skin Contact No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water

for 5 minutes. If irritation persists, obtain medicaladvise.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Causes skin irritation. May cause nose, throat & respiratory tract irritation. Direct contact

with eyes may cause temporaryirritation.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat according to person's condition & specifics of exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire Use carbon dioxide (CO2), dry chemical or water spray.

Large Fire Use dry chemical, foam or waterspray.

Unsuitable Extinguishing Media Notdetermined.

Specific Hazards Arising from the Chemical

Not determined.

Hazardous combustion productsCarbon oxides & traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

Protective Equipment and Precautions for Firefighters

Self-contained breathing apparatus & protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and EmergencyProcedures

Personal Precautions Observe all personal protection equipment recommendations described in Sections 5 & 8.

Environmental Precautions See Section 12 for additional ecological information.

Methods and Material for Containment and CleaningUp

Methods for Containment Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Cleaning Up Wipe up or scrape up & contain for salvage or disposal. Clean area as appropriate since

spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state & federal laws & regulations may apply to releases & disposal of this material as well as those materials & items employed in the cleanup of releases. You will need to determine which federal, state

& local laws & regulations are applicable. Sections 13 & 15 of this MSDS provide

information regarding certain federal & state requirements.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wash face, hands,

and any exposed skin thoroughly after handling. Use personal protection recommended in Section 8. Use only in well-ventilated areas. Avoid contact with skin and eyes. Product

evolves acetic acid (HOAc) when exposed to water orhumidair.

Conditions for Safe Storage, Including anylncompatibilities

Storage Conditions Keep container closed & store away from water ormoisture.

Incompatible Materials Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous

vapors to form as described in Section 8.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Amorphous silica(glass) 7631-86-9	-	(vacated) TWA: 6 mg/m³<1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO2) mg/m³TWA	IDLH: 3000 mg/m³ TWA: 6 mg/m³
Titanium Dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³total dust	IDLH: 5000 mg/m ³

Other Information Acetic acid is formed upon contact w/ water or humid air. Provide adequate ventilation to

control exposures within guidelines of OSHA PEL: TWA 10 ppm & ACGIH TLV: TWA 10

ppm, STEL 15 ppm.

Appropriate Engineering Controls

Ventilation must be adequate to maintain the ambient workplace atmosphere below the **Engineering Controls**

exposure limit(s) outlined in the SDS. Good general ventilation should be sufficient.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection Safety glasses as a minimum forprotection.

Skin and Body Protection Wear suitable protective clothing.

Respiratory Protection No special equipmentneeded.

General Hygiene Considerations Note: These precautions are for room temperature handling. Use @ elevated temperature

> or aerosol/spray applications may require added precautions. Handle in accordance with good industrial hygiene and safety practice. Wash @ mealtime & end of shift. Contaminated clothing & shoes should be removed as soon as practical & thoroughly cleaned before

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Paste

Appearance Clear/opaque or colored paste Odor Acetic Acid Odor (Vinegar

odor)

Color Various Odor threshold Not determined

Property Remarks • Method Values

Not determined Melting point/freezing point Not determined Boiling point/boiling range Not determined Flash point **Evaporation rate**

Flammability (solid, gas)

Flammability limits in air

Not applicable Not determined Not determined Upper flammabilitylimits
Lower flammabilitylimit

Vapor pressure
Vapor density

Not determined
Not determined
Not determined
Not determined

Specific gravity ~1.04

Water solubility Not determined Solubility in other solvents Not determined **Partition coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined Kinematic viscosity Not determined **Dynamic viscosity** Not determined **Explosive properties** Not determined **Oxidizing Properties** Not determined

Other Information

Additional information Note: The above information is not intended for use in preparing product specifications

VOC Content (%) < 3%/wt (< 40 g/L)

10. STABILITY AND REACTIVITY

@ 25 °C (77 °F)

Reactivity

Not reactive under normal conditions

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normalprocessing.

Hazardous polymerization Hazardous polymerization does notoccur.

Conditions to Avoid

Incompatible Materials.

Incompatible Materials

Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides & traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde, Nitrogen oxides & metaloxides.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Inhalation May cause irritation of respiratory tract.

Eye Contact May cause temporary irritation on eyecontact.

Skin Contact Causes skin irritation. Can be absorbed through the skin.

Ingestion Can be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Amorphous silica (glass) 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat)1 h
Polydimethylsiloxane 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg (Rabbit)	-
Methyltriacetoxysilane 4253-34-3	= 2060 mg/kg (Rat)	-	-
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-termExposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Amorphous silica (glass) 7631-86-9		Group 3		
Titanium Dioxide 13463-67-7		Group 2B		Х

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as humancarcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical Measures of Toxicity-Product

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal

Chemical Name	Algae/aquatic plants	Fish	Toxicityto microorganisms	Crustacea
Amorphous silica (glass)	440: 72 h	5000: 96 h Brachydanio rerio		7600: 48 h Ceriodaphnia
7631-86-9	Pseudokirchneriella	mg/L LC50 static		dubia mg/L EC50
	subcapitata mg/LEC50			

Persistence and Degradability

Complete information is not yetavailable.

Bioaccumulation

Complete information is not yetavailable.

Mobility

Complete information is not yetavailable.

Other Adverse Effects Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and specialcircumstances

DOT Not regulated

<u>IATA</u> Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressurehazard No
Reactive Hazard No

US State Regulations

Chemical Name	California Proposition 65
Titanium Dioxide -13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Amorphous silica(glass)	X	X	X
7631-86-9			

Titanium Dioxide	X	X	X
13463-67-7			

U.S. EPA Label Information

_	_	\sim T		INTE	-00		TIO	
- 1	n.	OΙ	HER	INF	·UK	IVI A	ПО	N

NFPAHealth HazardsFlammabilityInstabilitySpecial Hazards110Not determinedHMISHealth HazardsFlammabilityPhysical HazardsPersonal Protection100B- Safety Glasses,
Gloves

Issue Date 13-Dec-2012
Revision Date 11-Jun-2015
Revision Note

New format Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed onlyas a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warrantyor quality specification. The information relates onlyto the specific material designated and may not be valid for such material used in combination with anyother materials or in any process, unless specified in the text.

End of Safety Data Sheet