<b>ASHLAND</b>	Page: 1
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

#### 29 CFR 1910.1200 (OSHA HazCom 2012)

# SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### **Product identifier**

Trade name

: Valvoline<sup>™</sup> SAE 30 NON-DETERGENT MOTOR OIL

# Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

## **GHS Label element**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

#### Other hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature

: Defatter

#### Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED		Not a hazardous substance or mixture.	15.05

ASHLAND.	Page: 2
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline <sup>™</sup> SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

# SECTION 4. FIRST AID MEASURES

General advice	:	No hazards which require special first aid measures.
If inhaled	:	If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye.
If swallowed	:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Dizziness
Notes to physician	:	No hazards which require special first aid measures.

# SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	<ul> <li>Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.</li> <li>Water spray</li> <li>Foam</li> <li>Carbon dioxide (CO2)</li> <li>Dry chemical</li> </ul>
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: carbon dioxide and carbon monoxide Hydrocarbons
Specific extinguishing methods	:

<b>ASHLAND</b>	Page: 3
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

Product is compatible with standard fire-fighting agents.

Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Persons not wearing protective equipment should be ex from area of spill until clean-up has been completed.	kcluded
Environmental precautions	Prevent further leakage or spillage if safe to do so.	
Methods and materials for containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	gel,
Other information	Comply with all applicable federal, state, and local regu	lations.

#### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<ul> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>For personal protection see section 8.</li> </ul>
Conditions for safe storage	: Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: No materials to be especially mentioned.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
RESIDUAL OILS (PETROLEUM), SOLVENT- DEWAXED	64742-62-7	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3	OSHA_TRA

<b>ASHLAND</b>	Page: 4
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

	Mist.	NS
Engineering measures	eneral room ventilation should be adequa onditions of use. However, if unusual ope kist, provide sufficient mechanical (genera khaust) ventilation to maintain exposure be uidelines (if applicable) or below levels that uspected or apparent adverse effects.	rating conditions I and/or local elow exposure
Personal protective equipme		
Respiratory protection	o personal respiratory protective equipme quired.	nt normally
Eye protection	ot required under normal conditions of use oof safety goggles if material could be min to eyes.	•
Skin and body protection	/ear as appropriate: afety shoes /ear resistant gloves (consult your safety e upplier).	equipment
Hygiene measures	eneral industrial hygiene practice.	

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: amber
Odour	: No data available
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 424.99 °F / 218.33 °C (1,013.3333333 hPa)
Flash point	Calculated Phase Transition Liquid/Gas : > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) GLP: Calculated Explosive Limit

<b>ASHLAND</b>	Page: 5
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline <sup>™</sup> SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

Lower explosion limit	: 1 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 1.33333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: <1AIR=1
Relative density	: 0.888 (15.6 °C)
Density	: 0.8890 g/cm3 (15.56 °C)
Solubility(ies) Water solubility	: negligible
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Thermal decomposition	:
	No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide

# SECTION 11. TOXICOLOGICAL INFORMATION

<b>ASHLAND</b>	Page:
SAFETY DATA SHEET	Revision Date: 06/01/201
	Print Date: 11/2/201
	SDS Number: R016970
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.
3048	

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact
		Ingestion

#### Acute toxicity

Not classified based on available information. **Components:** RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Not classified as acutely toxic by inhalation under GHS. Remarks: No mortality observed at this dose. Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose. LD 50 (Rabbit): > 2,000 mg/kg Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

#### Skin corrosion/irritation

Not classified based on available information. Product:

Result: Repeated exposure may cause skin dryness or cracking.

#### **Components:**

**RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:** Species: Rabbit Result: Not irritating to skin

Serious eye damage/eye irritation Not classified based on available information. Product:

Remarks: Unlikely to cause eye irritation or injury.

Components: **RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:** Species: Rabbit Result: Not irritating to eyes

#### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. **Components:** RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Test Type: Buehler Test Species: Guinea pig Assessment: Does not cause skin sensitisation.

<b>ASHLAND</b>	Page: 7
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. **Reproductive toxicity** Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. Components: RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: No aspiration toxicity classification **Further information** Product: Remarks: No data available Carcinogenicity: IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. **OSHA** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. NTP No component of this product present at levels greater than or

#### **SECTION 12. ECOLOGICAL INFORMATION**

Ecotoxicity	
<u>Components:</u> RESIDUAL OILS (PETROLEUN	
Toxicity to fish	<ul> <li>SOLVENT-DEWAXED.</li> <li>LL50 (Pimephales promelas (fathead minnow)): &gt; 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility</li> </ul>
Toxicity to daphnia and other aquatic invertebrates	<ul> <li>EL50 (Daphnia magna (Water flea)): &gt; 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF</li> </ul>

by NTP.

equal to 0.1% is identified as a known or anticipated carcinogen

<b>ASHLAND</b>	Page: 8
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

Method: OECD Test Guideline 202

Toxicity to algae :	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic : toxicity)	NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211
Persistence and degradability	
<u>Components:</u>	
RESIDUAL OILS (PETROLEUM	) SOLVENT-DEWAXED:

	$\mathcal{S}$
Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 2 - 4 %
	Exposure time: 28 d
	Method: OECD Test Guideline 301B

#### Bioaccumulative potential

# Components:

No data available

#### Mobility in soil

<u>Components:</u> No data available

#### Other adverse effects

No data available

<u>Product:</u> Additional ecological information

: No data available

#### **Components:**

# SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

General advice

: Dispose of in accordance with all applicable local, state and federal regulations.

<b>ASHLAND</b>	Page: 9
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

Contaminated packaging : Empty remaining contents.

### **SECTION 14. TRANSPORT INFORMATION**

#### International transport regulations

#### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

#### U.S. DOT - ROAD

Not dangerous goods

#### U.S. DOT - RAIL

Not dangerous goods

#### U.S. DOT - INLAND WATERWAYS

Not dangerous goods

#### **TRANSPORT CANADA - ROAD**

Not dangerous goods

#### **TRANSPORT CANADA - RAIL**

Not dangerous goods

#### TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

#### INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

# MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

<b>ASHLAND</b>	Page: 10
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

#### \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant no	10
---------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313 Component(s)SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65		Proposition 65 warnings are not required for this product based on the results of a risk assessment.
<b>The components of this prod</b> TSCA		on TSCA Inventory
DSL	:	All components of this product are on the Canadian DSL.
AUSTR	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
KECL	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory

#### Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

<b>ASHLAND</b>	Page: 11
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

# **SECTION 16. OTHER INFORMATION**

#### Further information

Revision Date: 06/01/2015



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

# Full text of H-Statements referred to under sections 2 and 3.H315Causes skin irritation.

Further information

Sources of key data used to compile the Safety Data Sheet Ashland internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet : ACGIH : American Conference of Industrial Hygienists BEI : Biological Exposure Index CAS : Chemical Abstracts Service (Division of the American Chemical Society). CMR : Carcinogenic, Mutagenic or Toxic for Reproduction FG : Food grade GHS : Globally Harmonized System of Classification and Labeling of Chemicals. H-statement : Hazard Statement IATA : International Air Transport Association.

<b>ASHLAND</b>	Page: 12
SAFETY DATA SHEET	Revision Date: 06/01/2015
	Print Date: 11/2/2015
	SDS Number: R0169702
Valvoline™ SAE 30 NON-DETERGENT MOTOR OIL	Version: 1.1
3048	

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL : Occupational Exposure Limit** P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA: Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System