

AUG 11 2016

# SAFETY DATA SHEET

EASY-OFF® FUME FREE OVEN CLEANER



HEALTH • HYGIENE • HOME

## 1. Product and company identification

- Product name** : EASY-OFF® FUME FREE OVEN CLEANER
- Distributed by** : Reckitt Benckiser LLC.  
Morris Corporate Center IV  
399 Interpace Parkway (P.O. Box 225)  
Parsippany, New Jersey 07054-0225  
+1 973 404 2600
- Emergency telephone number (Medical)** : 1-800-338-6167
- Emergency telephone number (Transport)** : 1-800-424-9300 (U.S. & Canada) CHEMTREC  
Outside U.S. and Canada (North America), call Chemtrec:703-527-3887
- Website:** : <http://www.rbnainfo.com>
- Product use** : Oven Cleaner

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

- SDS #** : D0059366 v5.0
- Formulation #:** : 363915 v6.0
- UPC Code / Sizes** : 14.5 oz., 16 oz.; 24 oz. Aerosol Cans

## 2. Hazards identification

- Classification of the substance or mixture** : FLAMMABLE AEROSOLS - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1

### GHS label elements

**Hazard pictograms** :



- Signal word** : Warning
- Hazard statements** : Flammable aerosol.  
Causes serious eye irritation.  
May cause an allergic skin reaction.

### Precautionary statements

D0059366 v5.0

## 2. Hazards identification

- General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
- Response** : IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention/advice.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention/advice.
- Storage** : Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : None known.
- Hazards not otherwise classified** : None known.

## 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
2-(2-butoxyethoxy)ethanol	5 - 10	112-34-5
potassium carbonate	2.5 - 5	584-08-7
2-aminoethanol	2.5 - 5	141-43-5
isobutane	2.5 - 5	75-28-5
d-Limonene	0.1 - 1	5989-27-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

D0059366 v5.0

## 4. First aid measures

- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move to fresh air. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

D0059366 v5.0

## 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

D0059366 v5.0

## 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

- Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls/personal protection

### Control

#### Occupational exposure limits

Ingredient name	Exposure limits
2-(2-butoxyethoxy)ethanol	<b>ACGIH TLV (United States, 6/2013).</b> TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor
2-aminoethanol	<b>ACGIH TLV (United States, 6/2013).</b> TWA: 3 ppm 8 hours. TWA: 7.5 mg/m <sup>3</sup> 8 hours. STEL: 6 ppm 15 minutes. STEL: 15 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 3 ppm 8 hours. TWA: 8 mg/m <sup>3</sup> 8 hours. STEL: 6 ppm 15 minutes. STEL: 15 mg/m <sup>3</sup> 15 minutes. <b>NIOSH REL (United States, 10/2013).</b> TWA: 3 ppm 10 hours. TWA: 8 mg/m <sup>3</sup> 10 hours. STEL: 6 ppm 15 minutes. STEL: 15 mg/m <sup>3</sup> 15 minutes. <b>OSHA PEL (United States, 2/2013).</b> TWA: 3 ppm 8 hours.

D0059366 v5.0

## 8. Exposure controls/personal protection

isobutane

TWA: 6 mg/m<sup>3</sup> 8 hours.

**NIOSH REL (United States, 10/2013).**

TWA: 800 ppm 10 hours.

TWA: 1900 mg/m<sup>3</sup> 10 hours.

**ACGIH TLV (United States, 6/2013).**

STEL: 1000 ppm 15 minutes.

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eyeface protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

D0059366 v5.0

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	: Liquid. [Liquefied compressed gas.]
<b>Color</b>	: White.
<b>Odor</b>	: Lemon-like.
<b>Odor threshold</b>	: Not available.
<b>pH</b>	: 12.5 [Conc. (% w/w): 100%][25°C]
<b>Melting point</b>	: Not available.
<b>Boiling point</b>	: Not available.
<b>Flash point</b>	: Open cup: >93.3°C (>199.9°F) [Concentration]
<b>Evaporation rate</b>	: Not available.
<b>Flammability (solid, gas)</b>	: Not available.
<b>Lower and upper explosive (flammable) limits</b>	: Not available.
<b>Vapor pressure</b>	: Not available.
<b>Vapor density</b>	: Not available.
<b>Relative density</b>	: 0.994 to 1.07
<b>Solubility</b>	: Easily soluble in the following materials: cold water and hot water.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.

### Aerosol product

<b>Type of aerosol</b>	: Foam
<b>Heat of combustion</b>	: 4.594 kJ/g

## 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur. Polymerization. : There are no data available on the mixture itself.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame).
<b>Incompatible materials</b>	: Do not mix with household chemicals
<b>Hazardous decomposition products</b>	: Hazardous decomposition products : carbon oxides , Various Organic chemicals.

D0059366 v5.0

# 11. Toxicological information

## Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
potassium carbonate	LD50 Oral	Rat	1870 mg/kg	-
	LD50 Oral	Rat	1720 mg/kg	-
2-aminoethanol	LD50 Oral	Rabbit	>5000 mg/kg	-
d-Limonene	LD50 Dermal	Rabbit	>5000 mg/kg	-
*EASY-OFF® FUME FREE OVEN CLEANER	LD50 Oral	Rat	4400 mg/kg	-
	LC50 Inhalation Vapor	Rat	>200 mg/l	24 hours
	LD50 Oral	Rat	>5000 mg/kg	-

**Conclusion/Summary** : Not classified Harmful. \*Information is based on toxicity test result of the concentrate of a similar product.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
2-aminoethanol	Eyes - Severe irritant	Rabbit	-	250 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	505 milligrams	-
d-Limonene	Skin - Mild irritant	Rabbit	-	24 hours 10 Percent	-
	Eyes - Edema of the conjunctivae	Rabbit	4	-	7 days
*EASY-OFF® FUME FREE OVEN CLEANER	Skin - Non-irritant to skin.	Rabbit	0.59	-	-

### Conclusion/Summary

**Skin** : Non-irritant to skin.  
\*Information is based on toxicity test result of the concentrate of a similar product.

**Eyes** : Irritating to eyes.  
\*Information is based on toxicity test result of the concentrate of a similar product.

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
d-Limonene	-	3	-

### Reproductive toxicity

Not available.



D0059366 v5.0

## 11. Toxicological information

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Name	Result
d-Limonene	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

D0059366 v5.0

## 11. Toxicological information

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Dermal	37894.7 mg/kg

## 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
2-(2-butoxyethoxy)ethanol potassium carbonate	Acute LC50 1300000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 630000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
2-aminoethanol	Acute LC50 650000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 8.42 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	Acute LC50 >100000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
d-Limonene	Acute LC50 170000 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Acute EC50 421 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 688 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours

### Persistence and degradability

Not available.

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	low
2-aminoethanol	-1.31	-	low
d-Limonene	4.38	1022	high

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

D0059366 v5.0






## 12. Ecological information

**Other adverse effects** : No known significant effects or critical hazards.

## 13. Disposal considerations

**Disposal methods** : Waste packaging should be recycled. Waste must be disposed of in accordance with federal, state and local environmental control regulations.

## 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	UN1950	Aerosols, flammable	2.1	-		<u>Limited quantity</u>
<b>TDG Classification</b>	UN1950	Aerosols, flammable	2.1	-		<u>Limited quantity</u>
<b>Mexico Classification</b>	UN1950	Aerosols, flammable	2.1	-		<u>Limited quantity</u>
<b>IMDG Class</b>	UN1950	Aerosols, flammable	2.1	-		<u>Limited quantity</u>
<b>IATA-DGR Class</b>	UN1950	Aerosols, flammable	2.1	-		<u>See DG-List.</u>

PG\* : Packing group

## 15. Regulatory information

**U.S. Federal regulations** : TSCA 8(a) PAIR: 1,1'-oxydipropen-2-ol; pentane  
 TSCA 8(a) CDR Exempt/Partial exemption: Not determined  
 United States inventory (TSCA 8b): Not determined.  
 Clean Air Act (CAA) 112 regulated flammable substances: isobutane

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

D0059366 v5.0

## 15. Regulatory information

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : Fire hazard  
Immediate (acute) health hazard

#### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
2-(2-butoxyethoxy)ethanol	5 - 10	Yes.	No.	No.	Yes.	No.
potassium carbonate	2.5 - 5	No.	No.	No.	Yes.	No.
2-aminoethanol	2.5 - 5	Yes.	No.	No.	Yes.	No.
d-Limonene	0.1 - 1	Yes.	No.	No.	Yes.	No.

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	2-(2-butoxyethoxy)ethanol	112-34-5	7.125
<b>Supplier notification</b>	2-(2-butoxyethoxy)ethanol	112-34-5	7.125

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

- Massachusetts** : The following components are listed: ETHANOLAMINE; ISOBUTANE
- New York** : None of the components are listed.
- New Jersey** : The following components are listed: ETHANOLAMINE; ETHANOL, 2-AMINO-; GLYCOL ETHERS; Isobutane; PROPANE, 2-METHYL-
- Pennsylvania** : The following components are listed: ETHANOL, 2-AMINO-; GLYCOL ETHERS; PROPANE, 2-METHYL-

### Label elements

- Signal word** : CAUTION
- Hazard statements** : Eye Irritant  
CONTENTS UNDER PRESSURE.

D0059366 v5.0

## 15. Regulatory information

**Precautionary measures** : Keep out of the reach of children. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120 °F. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Do not get in eyes. Wash thoroughly after handling.

## 16. Other information

**Hazardous Material Information System (U.S.A.)** :

Health	2
Flammability	1
Physical hazards	0
Personal protection	D

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



NFPA (30B) aerosol Flammability Level 1

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Date of issue** : 13/10/2014.  
**Date of previous issue** : 08/05/2013  
**Version** : 5  
**Prepared by** : Reckitt Benckiser LLC.  
 Product Safety Department  
 1 Philips Parkway  
 Montvale, New Jersey 07646-1810 USA.  
 FAX: 201-476-7770

**Revision comments** : Update as per US GHS.

**Code #** : FF363915\_6  
 (D0059366 v5.0)\_US  
 GHS  
**SDS #** : D0059366 v5.0  
**Date of issue** : 13/10/2014.  
 13/14

D0059366 v5.0

## 16. Other information

✓ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.