

MATERIAL SAFETY DATA SHEET

2/18/16

1. Product and Company Identification

Material name STATIC GUARD ANTISTATIC SPRAY
Revision date 03-Mar-2010
CAS # Mixture
Product use ANTI-STATIC SPRAY
Company information ALBERTO-CULVER USA, INC.
2525 Armitage Avenue
Melrose Park, IL 60160 US
Business Phone (708) 450-3000
Emergency Phone (708) 450-3175
Shipping Emergencies CHEMTREC 800 424-9300 or 703 527-3887

Emergency Emergency Phone (708) 450-3175
Shipping Emergencies CHEMTREC 800 424-9300 or 703 527-3887

General information Business Phone (708) 450-3000

Static Guard
Antistatic SPRAY

2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE.
EXTREMELY FLAMMABLE. Will be easily ignited by heat, spark or flames.

Contact with eyes may cause irritation.

Potential short term health effects

Eyes Contact with eyes may cause irritation. Health injuries are not known or expected under normal use.

Skin Health injuries are not known or expected under normal use.

Inhalation Health injuries are not known or expected under normal use. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Ingestion Do not ingest. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Health injuries are not known or expected under normal use.

Target organs Central nervous system. Eyes. Respiratory system. Skin.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

Main symptoms Conjunctivitis. Rash. Irritation. Defatting of the skin. Narcosis. Behavioral changes. Decrease in motor functions.

3. Composition / Information on Ingredients

Components	CAS #	Percent
ALCOHOL DENAT.	64-17-5	< 80
Isobutane	75-28-5	< 10
Hydrofluorocarbon 152A	75-37-6	< 20
Propane	74-98-6	< 2.5

Composition comments This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

4. First Aid Measures

First aid

Eye contact Immediately flush eyes with plenty of water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Skin contact Wash off with soap and water. Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Ingestion Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If ingestion of a large amount does occur, seek medical attention.

Notes to physician Symptoms may be delayed.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a physician if symptoms develop or persist. If you feel unwell, seek medical advice (show the label where possible).

5. Fire Fighting Measures

Unusual fire & explosion hazards Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard. Containers may explode when heated.

Suitable extinguishing media Small Fires: Dry chemical, CO₂, water spray or regular foam.

Large Fires: Water spray, fog or regular foam.

Fire fighting equipment/instructions Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. ALWAYS stay away from tanks engulfed in flame. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire.

Special protective equipment for fire-fighters Structural firefighters protective clothing will only provide limited protection.

Specific methods In the event of fire and/or explosion do not breathe fumes.

Flash point > -58 °F (> -50 °C) Propellant

Auto-ignition temperature 685.4 °F (362.8 °C) estimated

6. Accidental Release Measures

Containment procedures Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Personal precautions Ventilate closed spaces before entering. Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep out of low areas. Stay upwind.

Methods for cleaning up Large Spills: Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling Do not handle or store near an open flame, heat or other sources of ignition. Vapors may form explosive mixtures with air. All equipment used when handling the product must be grounded. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking. May be ignited by open flame. Do not breathe gas/fumes/vapor/spray.

Storage Do not handle or store near an open flame, heat or other sources of ignition. Store in cool place. Keep in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. The pressure in sealed containers can increase under the influence of heat. Use care in handling/storage. Keep the container dry. Keep this material away from food, drink and animal feed. Keep out of the reach of children.

Level 2 Aerosol

8. Exposure Controls / Personal Protection

Personal protective equipment

Respiratory protection No personal respiratory protective equipment normally required. Applicable for industrial settings only. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection Not normally needed. Applicable for industrial settings only. Protective gloves.

Eye protection Avoid contact with eyes. Applicable for industrial settings only. Wear chemical goggles.

Skin and body protection Not normally needed. Applicable for industrial settings only. Use personal protective equipment as required.

Engineering measures to reduce exposure Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment if high dust/air concentrations are possible. Use explosion-proof ventilation equipment.

Hygiene measures Avoid contact with eyes. When using do not smoke. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Boiling point > 1.4 °F (> -17.2 °C)
Flammability Not available.
Form Aerosol.
Percent volatile 90.6097 % estimated
Vapor pressure 47 - 57 psi At 70°F
VOC 79.506 %

10. Chemical Stability & Reactivity Information

Stability Risk of explosion. Risk of ignition.
Incompatibility Acids. Amines. Isocyanates. Strong oxidizing agents.

11. Toxicological Information

Toxicology data for the preparation

Local effects Contact may irritate or burn eyes.
Carcinogenicity
US ACGIH Threshold Limit Values: A4 carcinogen
ALCOHOL DENAT. 64-17-5 Group A4 Not classifiable as a human carcinogen.
Reproductivity Possible reproductive hazard.
Chronic toxicity Prolonged exposure may cause chronic effects.
Further information Symptoms may be delayed.

12. Ecological Information

Ecotoxicity This material is not expected to be harmful to aquatic life. Components of this product have been identified as having potential environmental concerns.

Invertebrate Toxicity: EC50 value

ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 1.58 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 4 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 2 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 10000 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 10000 mg/l 48 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) 7.7 - 11.2 mg/l 48 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia obtusa) 10100 - 11200 mg/l 48 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia obtusa) 12300 - 13400 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 6 h Static Intoxication

Micro-organisms Toxicity: LC50 value

ALCOHOL DENAT.	64-17-5	Turbellarian, flatworm (Dugesia tigrina) > 100 mg/l 96 h Static Mortality
----------------	---------	---

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
Disposal instructions Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. If discarded, this product is considered a RCRA ignitable waste, D001. Incinerate the material under controlled conditions in an approved incinerator.

14. Transport Information

Department of Transportation (DOT) Requirements

<= 1L (33.8 Fl. Oz)

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D

Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306

Packaging non bulk 156, 306

Packaging bulk None

ERG number 126

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1

UN number UN1950

Additional information:

Special provisions 153, N82

Packaging exceptions 306

Packaging non bulk None

Packaging bulk None

ERG number 126



IATA

<= 1L (33.8 Fl. Oz)

Basic shipping requirements:


Proper shipping name Consumer commodity

Hazard class 9

Subsidiary hazard class 3

UN number ID8000

Packaging instructions 910



IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1

Subsidiary hazard class 6.1

UN number 1950

Packaging instructions Forbidden



IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS, flammable

Hazard class 2.1

Subsidiary hazard class 3

UN number 1950

Additional information:

Item 5F

Labels required 2.1

Transport Category 2



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200
hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely
hazardous substance No

Section 311 hazardous
chemical Yes

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

HMS ratings
Health: 1*
Flammability: 4
Physical hazard: 1

NFPA ratings
Health: 1
Flammability: 4
Instability: 1

International regulations The product is classified and labelled in accordance with EC directives or respective national laws.

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (CCS)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Japanese Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Korean Inventory of Chemicals (KICS)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

US - New Jersey Community RTK (EHS Survey): Reportable threshold

Hydrofluorocarbon 152A	75-37-6	500 LBS
Isobutane	75-28-5	500 LBS
Propane	74-98-6	500 LBS

US - Pennsylvania RTK - Hazardous Substances: Listed substance

ALCOHOL DENAT.	64-17-5	Listed.
Isobutane	75-28-5	Listed.
Propane	74-98-6	Listed.

16. Other Information

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date 03-Mar-2010