

SYSCO SATIN SHINE
STAINLESS STEEL CLEANER

Section I. Product Identification and Uses

HMIS (HFRP)
Health Hazard 1
Fire Hazard 1
Reactivity 0
Personal Protection b

Common / Trade name	SYSCO SATIN SHINE STAINL.STEEL SUPC 7206626	TDG	Class 2.1
WHMIS	A, D2A	PIN	UN 1950 AEROSOLS
Code	1999	PG	X
Material uses	Industrial applications: Stainless steel cleaner.		

Section II. Hazardous Ingredients

Name	CAS #	% by weight	TLV/PEL	LC50/LD50
Propane-Isobutane-N-Butane	74-98-6	10 - 20	Simple asphyxiant.	Not available.
Low odour mineral spirits.	64742-47-8	5 - 10	Not available.	ORAL (LD50): Acute: > 5000 mg/kg [Rat].

Section III. First Aid Measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin contact Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap.

Inhalation Remove to fresh air. Get medical attention.

Ingestion If ingested, do not induce vomiting. Have conscious person drink several glasses of water. Seek medical advice immediately and show the container or the label.

Section IV. Physical Data

Physical state and appearance	Aerosol.	Colour	Colorless.
pH (1% soln/water)	Not available	Odour	Characteristic.
pH (concentrate)	8.5-9.0	Volatility	Aerosol percent volatile: 83 to 84% VOC (W/W %): 37-41
Boiling point	100 to 205°C (212 to 401°F)	Vapour density	> 1 (Air = 1)
Specific gravity	0.93 to 0.97 (Water = 1)	Vapour pressure	5.332 to 6.665 kPa (40 to 50 mm Hg) (at 20°C)
Solubility	Not available		

Section V. Fire and Explosion Data

The product is Not a flammable as per canadian aerosols regulations

Auto-ignition temperature 347.8C based on odourless mineral spirit.

Flash points Not available.

Degradation products Hydrocarbon fumes and smoke. Carbon monoxide where combustion is incomplete.

Extinguishing media Use DRY chemicals, CO2, or foam.

Section VI. Reactivity data

Stability The product is stable.

Decomp. products See fire degradation products.

Reactivity Reactive to reactive with oxidizing agents.

Section VII. Toxicological properties

Route of entry Eye contact. Inhalation. Ingestion.

Toxicity for animals See section II

Acute effects Ingestion: May cause headache, nausea or weakness in case of long term exposure. Inhalation: Asphyxiant. Eye contact: May cause irritation. Skin contact: May cause irritation.

Chronic effects CARCINOGENIC EFFECTS: No ingredient in this product is currently listed as carcinogens by NTP or OSHA. Classified A3 (Proven for animal.) by ACGIH [Petroleum distillates, hydrotreated]. MUTAGENIC EFFECTS: No mutagenic effect. TERATOGENIC EFFECTS: No teratogenic or fetotoxic effects. Prolonged exposure may cause skin defatting.

Section VIII. Preventive measure

- Waste disposal** Do not puncture or incinerate containers, even when empty. Dispose of in accordance with local and federal regulations.
 - Storage** Compressed gases should be stored in a separate safety storage cabinet or room. Store in a cool, well ventilated area .
 - Precautions** Keep away from heat. Keep away from sources of ignition. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment.
 - Spill and leak** Try to stop the gaseous leak by taping the container with an appropriate material (tape, stretched plastic).Remove all sources of ignition. Absorb with an inert material. Use non sparking tools.
-

Section IX. Personal protective equipment

- Gloves** Gloves (impervious)
 - Respiratory** If used indoors on a continuous basis, use of a cartridge type respirator (NIOSH/MSHATC 23C or equivalent) is recommended.
 - Eyes** Safety glasses
 - Other** Not required
 - Eng. controls** Ventilation is normally required when handling or using this product.
-

Section X. Preparation and other Information

Validated by the Regulatory Affairs Department on July 15th 2012

EMERGENCY: EMERGENCY:CANUTEC 613-996-6666

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex A. Legend

- HMIS** Hazardous Materials Identification System
 - WHMIS** WHMIS Workplace Hazardous Materials Information System
 - TDG** Transport Dangerous Goods
 - PIN** Product Identification Number
 - PG** Packaging Group
-