Material Safety Data Sheet

Flash Point (Method Used)

Special Fire Fighting Procedures

Extinguishing Media

N/A = Not Applicable

over 200°F

Water fog, spray, dry chemical C02

Unusual Fire and Explosion Hazards Low when exposed to flames. May react with strong oxidizing materials

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U. S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

LEL

Do not enter confined fire space without protective equipment including NIOSH approved SCBA.

UEL

1.1

8.5

IDENTITY (As Used on Label and List)	Note: Blank spaces are not permitted. If any item is not applicable, or no	
READY-STRIP PLUS	information is available, the space must be marked to indicate that.	
SAFER PAINT & VARNISH REMOVER		
Section I		
Manufacturer's Name	Emergency Telephone Number (732) 792-2	001
Back to Nature Products Co.		
Div. of Dynacraft Industries Inc.		
Address (Number, Street, City, and ZIP Code)	Telephone Number for Information (732) 792-2001	
28 Harrison Ave. Suite 238		
Englishtown, New Jersey 07726		
	Date Prepared 01/01/07	
	Signature of Preparer (optional)	
Section II Hagardous Ingredients/Identity Infor	mation	
Section II-Hazardous Ingredients/Identity Information Hazardous Components (Specific Chemical Identity; Common Name(s)) OSHA PEL ACGIH TLV Other Limits % (optional)		
Hazardous Components (Specific Chemical Identity; Co.	mmon Name(s)) OSHA PEL ACGIH ILV Other	Limits % (optional)
Dimethyl Glutarate (1119-40-0)	Not Established	5-10%
Dimethyl Adipate (627-93-0)	Not Established	2-5%
N.Methyl-2 Pyrrolidone (872-50-4)	Not Established	10-15%
Non Toxic/Non Hazardous Components	N/A	65-80%
Section III- Physical/Chemical Characteristics		
Boiling Point 205° C	Specific Gravity (H ₂ 0=1) 1.15	
	Specific Gravity (H ₂ 0=1)	
Vapor Pressure (mm Hg.) .2 mm Hg at 20 °c (68° F)	Melting Point N/A	
Vapor Density (AIR =1) 5.5-6	Evaporation Rate (Butyl Acetate=1) .06	
Solubility in Water 70-80%	,	•
Appearance and Odor Very mild odor		
Section IV- Fire and Explosion Hazard Data		

Flammable Limits

Use water spray to cool fire exposed surfaces and to protect personnel.

Section V-Reactivity Data Stability Unstable **Conditions to Avoid** Strong oxidizing agents, fire, flame X Stable **Incompatibility** (Materials to Avoid) Strong oxidizing agents **Hazardous Decomposition or Byproducts** Unlikely Hazardous **May Occur Conditions to Avoid** N/A **Polymerization** Will Not Occur X **Section VI-Health Hazard Data Route(s) of Entry:** Inhalation? Skin? **Ingestion?** Eye Not established Not established Not established Eye Irritation **Health Hazards** (*Acute and Chronic*) Mildly to moderately irritating to eyes. Prolonged exposure to skin may cause irritation redness. NTP? IARC monographs? **OSHA Regulated? Carcinogenicity:** Not listed Not listed Not regulated Signs and Symptoms of Exposure: Very slow evaporation unlikely to reach exposure limits. **Acute Overexposure:** Dizziness, drowsiness unlikely due to very slow evaporation. May cause temporary blurring of vision. **Chronic overexposure:** Upper respiratory track irritation, lightheadedness. **Medical Conditions Generally Aggravated by Exposure** None established **Emergency and First Aid Procedures** Inhalation-remove victim to fresh air and provide oxygen if breathing is difficult. Eyes-flush exposed areas with large quantities of water. Skin-wash skin with soap and water. Use emollient skin creams. Ingestion-do not induce vomiting. Call Physician. Section VII-Precautions for Safe Handling and Use Steps to Be Taken in Case Material is Released or Spilled Soak up with suitable, non -reactive absorbant material, collect in suitable containers for disposal. Remove any source of high heat, sparks, flame. Recovered free liquid may be re-used or reclaimed. Dispose of in accordance with all Local, State and Federal regulations. Waste Disposal Method **Precautions to Be Taken in Handing and Storing** Store at room temperatures between 40°F-110°F, keep container tightly closed. Do not mix with strong oxidants, acids or alkalies. Do not reuse empty containers for other liquids. **Other Precautions Section VIII-Control Measures Respiratory Protection** (Specify Type) Use NIOSH approved chemical cartridge (organic vapor) respiratory equipment when spraying material (full face respirator is recommended) Ventilation Local Exhaust Sufficient to maintain air concentration as required by OSHA N/A **Special** Mechanical (General) Maintain adequate ventilation Other N/A **Protective Gloves** Butyl rubber, Neoprene gloves **Eye Protection** Eye protection for application and removal **Other Protective Clothing or Equipment** N/A

N/A = Not applicable.