

# Safety Data Sheet

Date of Revision: August 11, 2014



# Global Sealer Technologies

## SECTION 1. Identification

**Product Name:** GST International  
Wet Look Lacquer Low Sheen

**24 Hour Emergency:**  
INFOTRAC: 1-800-535-5053 Contract 93918

**Supplied by:** GST International, Inc.  
994 Packer Way  
Sparks, NV 89431  
775/829-2626

**Outside U.S. and Canada**  
**Infotrac: 352-323-3500**

NOTE: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

**Recommended Use:** Sealer for Concrete/Masonry

## SECTION 2. Hazard(s) Identification

\*\*\* EMERGENCY OVERVIEW \*\*\*: Extremely flammable liquid and vapor. May be fatal if swallowed. Suspect cancer hazard.

### GHS Classification

Carc. 2, Eye Irrit. 2, Flam. Liq. 2, Repr. 1A, STOT RE 2, STOT SE 3 NE, Skin Irrit. 2

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapor.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Reproductive Toxicity, category 1A	H360	May damage fertility or the unborn child.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

### GHS PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see first aid section on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### SECTION 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
2-propanone	67-64-1	50-75	GHS02-GHS07	H225-319-336
Xylene	1330-20-7	10-25	GHS02-GHS07-GHS08	H226-315-319-332-335-351-373
Petroleum hydrocarbon	64742-94-5	2.5-10	GHS02-GHS07-GHS08	H226-315-332-351-372
2-butoxyethanol	111-76-2	2.5-10	GHS02-GHS07-GHS08	H227-302-315-319-360
Ethylbenzene	100-41-4	1.0-2.5	GHS02-GHS07-GHS08	H225-315-319-332-335-351-373
2-ethylhexyl benzoate	5444-75-7	1.0-2.5	No Information	No Information
Naphthalene	91-20-3	0.1-1.0	GHS02-GHS06-GHS08	H226-302-315-320-330-351

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### SECTION 4. First-Aid Measures



**FIRST AID - EYE CONTACT:** Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

**FIRST AID - SKIN CONTACT:** Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately and clean shoes before reuse.

**FIRST AID - INHALATION:** Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

**FIRST AID - INGESTION:** Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

### SECTION 5. Fire-Fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Extremely flammable liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Closed container may explode under extreme heat.

**SPECIAL FIREFIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Evacuate all unnecessary personnel. Shut down motors, pumps, electrical service and eliminate all sources of ignition. Avoid use of solid water streams. Do not use water jet (frothing possible). Use water with

caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Small fires: Dry chemical, carbon dioxide, water spray or alcohol-resistant foam. Large fires: Water spray, water fog, and alcohol-resistant foam.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

## SECTION 6. Accidental Release Measures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Evacuate unnecessary personnel. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

## SECTION 7. Handling and Storage



**HANDLING:** Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Potential peroxide former. If peroxide formation is suspected, do not open or move container. Material accumulates static charge (ignition source). Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Use explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. After opening, purge container with nitrogen before reclosing. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

**STORAGE:** Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep container closed when not in use. Do not allow to evaporate to near dryness. Protect from direct sunlight. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

## SECTION 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
2-propanone	500 ppm	750 ppm	1000 ppm	N.D.
Xylene	100 ppm	150 ppm	100 ppm	N.D.
Petroleum hydrocarbon	N.D.	N.D.	N.D.	N.D.
2-butoxyethanol	20 ppm	N.D.	50 ppm	N.D.
Ethylbenzene	100ppm	125ppm	100ppm	N.D.
2-ethylhexyl benzoate	N.D.	N.D.	N.D.	N.D.
Naphthalene	10 ppm	15 ppm	10 ppm	15 ppm

### Personal Protection



**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of a respirator. NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.



**SKIN PROTECTION:** Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.



**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.



**OTHER PROTECTIVE EQUIPMENT:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



**HYGIENIC PRACTICES:** Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

## SECTION 9. Physical and Chemical Properties

<b>Appearance:</b>	Clear liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Typical	<b>Odor Threshold:</b>	N.D.
<b>Density, g/cm<sup>3</sup>:</b>	0.866	<b>pH:</b>	N.D.
<b>Freeze Point, °F:</b>	N.D.	<b>Viscosity:</b>	N.D.
<b>Solubility in Water:</b>	Partial	<b>Explosive Limits, vol%:</b>	0.8 - 12.8
<b>Boiling Range, °F:</b>	133 - 656	<b>Flash Point, °F:</b>	0
<b>Evaporation Rate:</b>	N.D.	<b>Auto-ignition Temp., °F:</b>	N.D.
<b>Vapor Density:</b>	N.D.	<b>Vapor Pressure:</b>	N.D.

(See "Other information" Section for abbreviation legend)

## SECTION 10. Stability and Reactivity

**STABILITY:** No Information

**CONDITIONS TO AVOID:** Avoid impact, friction, heat, sparks, flame and source of ignition. Minimize exposure to air.

**INCOMPATIBILITY:** Keep separate from alkalis. Prevent contact with halogens. Prevent contact with strong oxidizing agents. Keep away from acids. Avoid contact with concentrated sulfuric or nitric acid.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed. During combustion asphyxiants may be formed. Decomposition releases nitrogen oxides. May form peroxides of unknown stability.

**HAZARDOUS POLYMERIZATION:** No Information

## SECTION 11. Toxicological Information



### Information on Toxicological Effects

**EFFECTS OF OVEREXPOSURE - INHALATION:** Breathing saturated vapors for a few minutes may be fatal. Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation. Prolonged inhalation may be harmful. Breathing in the material may irritate the mucous membranes of the nose, throat bronchi and lungs. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). May cause dizziness and drowsiness.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Contact with skin may cause mild irritation. Causes skin irritation. May be absorbed in toxic amounts through the skin. Harmful if absorbed through skin. Can be absorbed through skin and produce central nervous system effects. Low order of toxicity. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes eye irritation. Symptoms may include stinging, tearing, redness and swelling.

**EFFECTS OF OVEREXPOSURE - INGESTION:** May be fatal if swallowed. Harmful or fatal if liquid is aspirated into lungs. Ingestion may cause gastrointestinal tract irritation. May cause nausea and diarrhea. Ingestion may result in nausea, vomiting, diarrhea and restlessness. May cause nausea and vomiting. May cause headache. May cause dizziness and drowsiness and/or stupor.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Animal carcinogen. Suspect cancer hazard. Possible brain damage from overexposure. The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. This product contains naphthalene. A National Toxicology Program (NTP) draft report states that lifetime inhalation exposure to naphthalene resulted in increases in tumors of the nose in rats. In a previous NTP study, lifetime inhalation exposure to naphthalene increased lung tumors in female mice. The relevance of the rodent findings to humans is questionable. Overexposure may cause nervous system damage. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Possible reproductive hazard. Overexposure may cause

kidney damage. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

**Primary Route(s) of Entry:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50, mg/L</u>
67-64-1	2-propanone	5800.0	20000.0	76.0
1330-20-7	Xylene	>3523	>4200	>20.0
64742-94-5	Petroleum hydrocarbon	>6,000	>2,000	>20.0
111-76-2	2-butoxyethanol	>470	>2,000	>450,220
100-41-4	Ethylbenzene	3500	15433	>20.0
5444-75-7	2-ethylhexyl benzoate	>2,000	>5,000	N.D.
91-20-3	Naphthalene	490	20000	>0.340

## SECTION 12. Ecological Information

ECOLOGICAL INFORMATION: No Information

## SECTION 13. Disposal Considerations



Always dispose of any waste in accordance with all local, state, and federal regulations.

**DISPOSAL METHOD:** Dispose of waste in accordance with all local, state and federal regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Evacuate unnecessary personnel. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

## SECTION 14. Transport Information

<b>DOT Proper Shipping Name:</b>	Paint	<b>Packing Group:</b>	II
<b>DOT Hazard Class:</b>	3	<b>Hazard SubClass:</b>	No Information
<b>DOT UN/NA Number:</b>	UN1263	<b>Resp. Guide Page:</b>	128

## SECTION 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

**Chemical Name****CAS-No.**

Xylene	1330-20-7
2-butoxyethanol	111-76-2
Ethylbenzene	100-41-4
Naphthalene	91-20-3
1,2,4 trimethylbenzene	95-63-6
1,2-ethanediol	107-21-1
Methanol	67-56-1
1-butanol	71-36-3

**TOXIC SUBSTANCES CONTROL ACT:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**Chemical Name****CAS-No.**

Naphthalene	91-20-3
2,2-oxybis-ethanol dibenzoate; diethylene glycol dibenzoate	120-55-8

**U.S. State Regulations:****NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

**Chemical Name****CAS-No.**

Poly(methyl methacrylate/n-butyl methacrylate/methacrylic acid	28262-63-7
--	------------

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product are at or greater than 3%.

**Chemical Name****CAS-No.**

Poly(methyl methacrylate/n-butyl methacrylate/methacrylic acid	28262-63-7
--	------------

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

**Chemical Name****CAS-No.**

Ethylbenzene	100-41-4
Naphthalene	91-20-3

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

**Chemical Name****CAS-No.**

Methanol	67-56-1
----------	---------

**International Regulations: As follows -****CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**WHMIS Class:** No Information

**SECTION 16. Other Information**

Revision Date: 8/11/2014 Supersedes Date: New SDS

Datasheet produced by: EH&S - Regulatory Department

**HMIS Ratings:**

<b>Health:</b>	2	<b>Flammability:</b>	3	<b>Reactivity:</b>	0 - No Hazard	<b>Personal Protection:</b>	X
----------------	---	----------------------	---	--------------------	---------------	-----------------------------	---





**Volatile Organic Compounds, gr/ltr:** 244

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/ REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H227 Combustible liquid
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H320 Causes eye irritation
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

- GHS02 
- GHS06 
- GHS07 
- GHS08 

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.