



# Safety Data Sheet

## BOSS® 801 Pool & Spa Silicone

### Section 1. Identification

Product Identifier	BOSS® 801 Pool & Spa Silicone		
Synonyms	80131; 80103; 80101; 80100; 80151; 80150; 02505CL10; 02505WH10; 02505GY10; 04073CL12; 03217CL01; 03217WH10; C04052CL; C04052GY; C04052WH		
Manufacturer Stock Numbers	02505CL10; 02505WH10; 02505GY10; 04073CL12; 03217CL01; 03217WH10; C04052CL; C04052GY; C04052WH		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact			
Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

### Section 2. Hazards Identification

Classification	EYE DAMAGE/IRRITATION - Category 2A HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD - Category 3 SENSITIZATION - SKIN - Category 1 SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2
Signal Word	Warning

## Pictogram



## Hazard Statements

Causes serious eye irritation  
Harmful to aquatic life with long lasting effects  
May cause an allergic skin reaction  
May cause damage to organs through prolonged or repeated exposure.

## Precautionary Statements

### Response

Get medical advice/attention if you feel unwell.  
If eye irritation persists: Get medical advice/attention.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If on skin: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Read label before use.  
Wash contaminated clothing before reuse.

### Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.  
Avoid release to the environment  
Contaminated work clothing must not be allowed out of the workplace.  
Do not breathe dust/fume/gas/mist/ vapors/spray.  
Wash hands thoroughly after handling.  
Wear eye protection/face protection.  
Wear protective gloves.

### Storage

N/A

### Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Additional Information None known

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
112945-52-5	Amorphous fumed silica	5% - 10%
64741-44-2	Distillates (petroleum), straight-run middle	5% - 10%
63148-62-9	Dimethylpolysiloxane	10% - 30%
2224-33-1	Vinyl Oximino Silane	1% - 5%
22984-54-9	Methyl Oximino Silane	1% - 5%
1760-24-3	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Eye Contact	Immediately flush with water for 15 minutes.
Skin Contact	Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Ingestion	Get medical attention.
Comments	Treat according to person's condition and specifics of exposure.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Carbon dioxide, dry chemical, foam, water, water fog or spray
Unsuitable Extinguishing Media	None known
Auto-ignition Temperature	Not determined
Lower Explosive Limit (%)	Not applicable
Upper Explosive Limit (%)	Not applicable
Special Fire Fighting Procedures	Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire or Explosion Hazards	None known

## Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

## Section 7. Handling and Storage

Storage	Keep container closed and store in a cool, well ventilated area, away from water or moisture.
Handling	Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Amorphous fumed silica	10 mg/m <sup>3</sup>	6 mg/m <sup>3</sup>	N/A
	Distillates (petroleum), straight-run middle	N/A	N/A	N/A
	Dimethylpolysiloxane	N/A	N/A	N/A
	Vinyl Oximino Silane	N/A	N/A	N/A
	Methyl Oximino Silane	N/A	N/A	N/A
	N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane	N/A	N/A	N/A

Personal Protective Equipment	Goggles
Component Exposure Limits	Methyl ethyl ketoxime is formed upon contact with water or moisture in the air. Provide adequate ventilation to control exposures to within the exposure guideline of 2 ppm (TWA).
Engineering Controls	Local Ventilation: Recommended General Ventilation: Recommended
Eye Protection	Use proper protection - safety glasses as a minimum.
Skin Protection	Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.
	Suitable Gloves: Silver Shield® 4H®
Respiratory Protection	Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.  Suitable Respirator: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.
Comment	Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime within the

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Refer to product label
Odor	Slight
Odor Threshold	N/A
Solubility	Insoluble
Partition coefficient Water/n-octanol	N/A
VOC%	26 g/L (<3%)
Viscosity	850,000 cPs
Specific Gravity	1.03
Density lbs/Gal	8.55
Pounds per Cubic Foot	N/A
Flash Point	Not determined
FP Method	N/A
pH	Not applicable
Melting Point	Not determined
Boiling Point	Not determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not determined
Vapor Density	Not determined

### Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Conditions to avoid	None known
Hazardous polymerization	Will not occur

Materials to Avoid /  
Incompatibility  
Chemical Stability

Oxidizing material can cause a reaction.  
Stable

## Section 11. Toxicological Information

**Special Hazard Information on Component** Methyl Oximino Silane (22984-54-9) Possible skin sensitizer  
Vinyl Oximino Silane (2224-33-1) Possible skin sensitizer

**Component Toxicology Information** Methyl Ethyl Ketoxime (MEKO) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver tumors. Since many commonly used chemicals cause liver tumors in rats and mice, additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

**Carcinogenicity** No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

**Mutagenicity** This product is not known to be a mutagen.

**Teratogenicity** This product is not known to be teratogenic.

**Reproductive Toxin** This product is not known to be a reproductive toxin.

## Section 12. Ecological Information

**Environmental Effects** Complete information is not yet available.

**Fate and Effects in Waste Water Treatment Plants** Complete information is not yet available.

**Environmental Fate and Distribution** Complete information is not yet available.

## Section 13. Disposal

**Waste Disposal Method** We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

## Section 14. Transport Information

**UN Number** N/A

**UN Proper Shipping Name** Not regulated

**DOT Classification** Not regulated

**Packing Group** Not regulated

Air Shipment (IATA) Not subject to IATA regulations.

Ocean Shipment (IMDG) Not subject to IMDG code.

## Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**TSCA Status** All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

**SARA Title III Section 302 Extremely Hazardous Substances** None

**SARA Title III Section 304 CERCLA Substances dangereuses** None

**SARA Title III Section 311/312** No components subject to 40 CFR 370

**SARA Title III Section 313 Toxic Chemicals** None present or none present in regulated quantities.

**California Prop 65** White and Colors  
WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the state of California to cause cancer and Methanol, which is known to the State of California to cause birth defects and other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Clear  
WARNING: This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects and other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Section 16. Other Information

**Revision Date** 6/1/2018

**Disclaimer** The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.