

The ServiceMaster Company
One ServiceMaster Way
Downers Grove, IL 60515

MATERIAL SAFETY DATA SHEET
IC 00446 with 29 CFR 1910.1201
1/800/333-6678

FiberFresh Gum Remover

SECTION I

Product (Trade) Name - FiberFresh Gum Remover
Manufacturer's Name - The ServiceMaster Company
Address - One ServiceMaster Way, Downers Grove, IL 60515
Emergency Telephone No - 1/800/333-6678
Chemical Name and Synonyms - N/A
Chemical Formula - N/A
DOT Hazard Class - Compressed Gases, Flammable, n.o.s. (isobutane, propane)
DOT ID Number - UN1954

SECTION II - HAZARDOUS INGREDIENTS

Ingredient	C.A.S. No.	Wt. by %	OSHA PEL	ACGIH TLV-TWA	Other Limit	Listed As Carcinogenic By IARC, NTP	OSHA ACGIH
Isobutane	75-28-5	30-40	800ppm	800ppm	N/E	No	
Propane	74-98-6	40-60	1000ppm	N/E	N/E	No	

In accordance with OSHA's Hazard Communication Standard, ingredients listed in this section are those identified as being hazardous and present at concentrations greater than 1%, or greater 0.1% if the substance is a listed carcinogen. Information concerning ingredients identified as "Proprietary" will be made available as provided in 29 CFR 1910.1200(h).

SECTION III -- PHYSICAL DATA

Boiling Point (°C): 42
Vapor Pressure (mm hg): N/D
Vapor Density (Air = 1): > 1
pH of Concentrate: N/A
Appearance and Odor: Clear odorless gas in aerosol can

Specific Gravity (H₂O = 1): 0.57
% Volatile by Weight: N/A
Evaporation Rate: N/D
Solubility in Water: Slight

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

USA Flame Projection Test (ASTM D 3065): > 24" Flashback
Flammable Limits: LEL UEL
N/A N/A

Extinguishing Media: Use water spray to keep containers cool. Contains an extremely flammable gas.
Special Fire Fighting Procedures: Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.
Unusual Fire and Explosion Hazards: Aerosol container (pressurized) may burst if heated over 120°F. Extremely flammable contents.

SECTION V -- HEALTH HAZARD DATA

Primary Route(s) of Exposure: Skin contact, inhalation.
Threshold Limit Value: N/D for mixture. See Section II for TLV's of hazardous ingredients.
Effects of Overexposure:

- Acute:** By Inhalation: May cause dizziness, lack of coordination, excitation, headache, nausea.
- By Eye Contact: Will cause cold or freezing sensation.
- By Ingestion: Ingestion may cause nausea, vomiting.
- By Skin Contact: Will cause cold or freezing sensation.
- Chronic:** None known.
- Medical Conditions Generally Aggravated by Exposure:** Persons with pre-existing skin disorders may be affected.

Emergency and First Aid Procedures:

- For Inhalation:** Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration.
- For Eye Contact:** Flush with plenty of water for at least 15 minutes lifting eyelids to ensure complete removal. Get immediate medical attention.
- For Ingestion:** Ingestion of product is not likely. Get medical attention.
- For Skin Contact:** Flush or immerse areas in lukewarm water. If skin is not burned, keep warm and stimulate circulation with massage. Get medical attention.

SECTION VI -- REACTIVITY DATA

Stability: Stable.
Conditions to Avoid: Extreme heat, direct sunlight, ignition sources
Incompatibility (Materials to Avoid): Strong oxidizers
Hazardous Decomposition Products: Oxides of carbon
Hazardous Polymerization: Will not occur

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released Or Spilled: Isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread.
Waste Disposal Method: Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.
Hazardous Waste Classification: N/A

SECTION VIII -- SPECIAL PROTECTION INFORMATION

For Handling Product as Supplied:
Respiratory Protection: Not usually necessary. Use with adequate ventilation. If PEL's or TLV's are exceeded, use an approved NIOSH/MSHA respirator.
Ventilation: Maintain general ventilation.
Protective Gloves: Wear rubber gloves if direct contact is possible.
Eye Protection: If contact is possible, wear chemical splash goggles.
Other Protective Equipment: Not usually necessary. If direct contact is possible, wear apron, boots, face shield, gloves, etc.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing: Store away from heat, sparks, open flame, and ignition sources.
Other Precautions: Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

Prepared By: Kevin T. Wagner
Title: Occupational Safety and Health Coordinator

Date Prepared: November 13, 1996
Supersedes previous form dated: October 3, 1995