Safety Data Sheet

According to GHS (Global Harmonized System) - Hazcom 2012

Date Printed (YYYY-MM-DD): 2018-01-31

Section 1 - Product and Company Information

Product Name: PlastiFix Liquid Product Part Number(s): 2520, 2520-L

Recommended Use: Part of a kit for repairing plastic

Revision Date (YYYY-MM-DD):

COMPANY IDENTIFICATION: EMERGENCY TELEPHONE NUMBER

Polyvance **24 Hour Emergency** Chemtrec - 1-800-424-9300 (Outside USA 703-527-3887)

Customer Information 256-638-4103 (7AM - 4PM (CST)

1128 Kirk Rd.

Number M-F)

Rainsville, AL 35986

Information Email: info@polyvance.com

Section 2 - Hazards Identification

Appearance: Colorless liquid


Odor: Acrid, penetrating odor.

Hazard Statement:

WARNING! . Highly flammable liquid and vapor. Causes mild skin irritation. Causes eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life.

Signal Word: WARNING!
Signal Word Hazard: Flammable Liquid

GHS Physical Hazard	GHS Health Hazard	GHS Environmental Hazard
Pictograms	Pictograms	Pictograms



GHS Hazards Statement Codes for This Product

Statement Type	Statement Code	Statement Text
Physical	H225	Highly flammable liquid and vapor
Health	H316	Causes mild skin irritation
Health	H320	Causes eye irritation
Health	H335	May cause respiratory irritation
Health	Н373	May cause damage to organs through prolonged or repeated exposure
Environmenta	l H402	Harmful to aquatic life

Precautionary Statement:

Keep away from heat/sparks/open flames/hot surfaces - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with soap and water. Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinereate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics..

GHS Precautionary Statement Codes for This Product

Statement Type	Statement Code	Statement Text
Prevention	P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
Prevention	P261	Avoid breathing dust/fume/gas/mist/vapours/spray
Prevention	P280	Wear protective gloves/protective clothing/eye protection/face protection
Response	P302+352	IF ON SKIN: Wash with soap and water
Disposal	P501	Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinereate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics.

Potential Health Effects

Eye Contact: Liquid and vapors can cause irritation (tears, blurred vision, redness) and

possible corneal damage.

Skin Contact: May cause skin irritation (itching and soreness).

Skin Absorption: May cause rashes.

Skin Sensitization: Can cause skin sensitization.

Inhalation: High concentration of vapors is severe irritant to respiratory tract and

may cause dizziness, headache and anaesthetic effects. It may cause

elevated methmoglobin in the blood.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and

gastrointestinal tract and abdominal pain, central nervous depression.

May cause methemoglobinemia.

Birth

Defects/Developmental

Effects:

Developmental toxicity observed in animal tests but only at levels toxic

to the mother.

Section 3 - Composition/Information on Ingredients

Component CAS # ENIECS REACH Reg. No. Am

Section 4 - First Aid Measures

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

Skin Contact: In case of contact, immediately wash skin with soap and water. Obtain medical attention if blistering occurs or redness persists. Wash contaminated clothing before reuse.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion: If swallowed, do not induce vomiting. Immediately give two glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Section 5 - Firefighting Measures

Extinguishing Media: Chemical foam, carbon dioxide, dry chemical

Fire Fighting Procedures: Wear self contained breathing apparatus, and full protective gear. Use water spray to cool containers.

Unusual Fire and Explosion Hazards: Vapors may travel to source of ignition and flash back. Heat can cause polymerization with rapid release of energy whey may rupture container explosively. (Spontaneous polymerization may occur on prolonged storage)

Section 6 - Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Evacuate the area. Eliminate sources of ignition. Use self contained breathing apparatus and protective clothing. Dike and absorb with inert material. Transfer to proper containers for disposal, use non-sparking tools.

Personal Precautions: Eliminate sources of ignition. Wear protective gloves and eye/face protection. Avoid breathing vapors. See Section 8

Environmental Precautions: Avoid release to the environment. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

Section 7 - Handling and Storage

General Handling: Do not breathe vapor or mist. Do not get in eyes, on skin or clothing. Wash thoroughly after handling. Keep out of reach of children.

Other Precautions: Close container after eash use. Ground container when pouring. Keep away from heat, sparks and flames.

Storage: Store in a cool dry place away from heat, sparks, flame and direct sunlight. Store in well-ventilated space. Keep container tightly closed. As long as the bottle is sealed and kept in a cool, dry place, shelf life should be indefinite.

Section 8 - Precautions to Control Exposure / Personal Protection

Component Source Type Value Remarks

Personal Protective Equipment (PPE):

Eye/Face Protection: Safety glasses or chemical splash goggles.

Skin Protection: Wear protective gloves. For splash protection: Butyl; EN374. For immersion protection: Butyl; 0.7 mm or greater; EN374

Respiratory Protection: Wear respiratory protection. Wear suitable pretective equipment if exposure to levels above the occupational exposure limit is likely. A suitable mask with filter type "A" may be appropriate.

Hygenic Measures: Wash face and hands thoroughly with soap and water after use and before eating, drinking, smoking or applying cosmetics.

Other Protection Measures: Provide eyewash, safety shower and impervious clothing.

Engineering Controls: Use good, local explosion-proof ventilation to ensure that the occupational exposure limit is not exceeded.







Section 9 - Physical and Chemical Properties

Appearance: Clear Liquid

Colorless Colorless

Odor: Acrid, penetrating odor

ph: Not Applicable

Flash Point: $11.5^{\circ} \text{ C } (52.7^{\circ} \text{ F})$

Upper Flammable Limit: 12.5

Lower Flammable Limit: 2.12

Autoignition Temperature: 421°C (790° F)

Vapor Pressure: 28 mm Hg @ 20 C (68 F)

Boiling Point: 101° C (214° F) at 760 mm Hg

Vapor Density: 3.5 @ 60F (Air = 1)

Specific Gravity: 0.98 g/ml @ 15.5 C (60 F)

Freezing Point: $-48^{\circ} \text{ C } (-54.4^{\circ} \text{ F})$

Melting Point: $-49^{\circ} \text{ C } (-56.2^{\circ} \text{ F})$

Solubility in Water: 27.6 WT% @ 20 C (68 F)

Evaporation Rate: 3.1 (BuAc = 1)

Partition Coefficient: 1.38

Decomposition Temperature: Not applicable

Visosity: Not applicable

Section 10 - Stability and Reactivity

Stability/Instability: Unstable with heat

Conditions To Avoid: Temps above 70 F (21 C), ignition sources, oxidizing/reducing agents, peroxides, acids, alkalis, amines, aging & contamination. Material is a strong solvent and can soften

paints and rubber.

Incompatible Materials: Reducing and oxidizing agents and UV light. Material has strong solvent properties and can soften paint and rubber.

Hazardous Polymerization: Can occur.

Hazardous Decomposition Products: Mainly oxides of carbon when burned.

Section 11 - Toxicological Information

Ingestion Toxicity: 7,900 mg/Kg in rats (very low toxicity by ingestion)

Skin Absorption:LD50: >35,500 mg/Kg in rabbits (very low toxicity by contact)

Inhalation

4 hour LD50: 7093 ppm in rats (very low toxicity by inhalation)

Repeated Dose Toxicity

Repeated exposure to high levels produces adverse effects on the heart, lungs, liver and kidneys.

Section 12 - Ecological Information

Movement & Partitioning

The product is predicted to have high mobility in soil.

Persistence and Degradability

Readily biodegradable.

ECOTOXICITY

Low toxicity to fish. Harmful to aquatic invertebrates. Low toxicity to algae.

Bioaccumulation:

Product has low potential for bioaccumulation.

Section 13 - Disposal Considerations

Disposal Method:

When discarded it is listed as a hazardous waste by the EPA under RCRA U-162 with the reportable quantity of 1000 pounds (40CFR Part 302) Incinerate liquid and diking material after addition of excess inhibitor, in accordance with regulations.

Container Disposal: Disposal must be made according to official regulations.

Section 14 - Transport Information

DOT

Proper Shipping Name: Methyl Methacrylate Monomer, stabilized

Hazard Class: 3.2 (9.2)

ID Number: UN1247

Packing Group: II

IMDG (Maritime transport)

IMDG Class: 3.2

UN Number: UN1247

Packaging Group: II

Proper Shipping Name: Methyl Methacrylate Monomer, stabilized

Additional IMDG Shipping Information: Packing instruction P001:

IATA (Air Transport)

ICAO/IATA Class: 3

UN/ID Number: UN1247

Label: Flammable Liquid

Air Packaging Group: II

Proper Shipping Name: Methyl methacrylate monomer, stabilized

Additional IATA Shipping Information: Packing instruction Y341: Inner packaging <0.5L. Total net

quantity per package: 1L.

Excepted Quantity (EQ) Code: E2: Maximum net quantity per inner packaging: 30 g / 30 mL.

Maximum net quantity per outer packaging: 500 g / 500 mL

Section 15 - Regulatory Information

Superfund Amendments and Reathorization Act of 1986 (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health HazardYesDelayed (Chronic) Health HazardNoFire HazardYesReactive HazardYesSudden Release of PressureNo


The following table list hazardous components and the regulatory lists for which they are required to be reported.

Component: Methyl Methacrylate Monomer

CAS Number: 80-62-6 **Amount:** 95-100%

Methyl Methacrylate Monomer is listed with Pennsylvania Right to Know.

HMIS Rating (Scale 0 - 4)



NFPA Ratings

Section 16 - Other Information

Legend

DISCLAIMER

This Safety Data Sheet (SDS) is prepared in compliance with GHS Hazcom 2012. The information may be based in part on information provided by component suppliers and is believed to be correct as of the data hereof. However, no warranty or merchantability, fitness for any use, or any other warranty is expressed is to be implied regarding the accuracy of of this data, the results to be obtained from the use of the material or the hazards connected with such use. Since the information contained herein my be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material is furnished on the condition that the person receiving shall make his/her own determination as the the suitability of the material for his/her particular purpose on the condition that he/she assume the risk of his/her use thereof.