



Material Safety Data Sheet

Revision Date 03-Mar-2014

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product code 53395
Product name High Solids Ford Tractor Blue Spray Paint
Recommended Use Coating
Supplier Lawson Products, Inc.
8770 W.Bryn Mawr Ave.- Suite 900
Chicago, IL 60631
1-866-529-7664
Emergency telephone number (888) 426-4851

2. HAZARDS IDENTIFICATION

Emergency Overview

Extremely flammable. Irritating to eyes. Irritating to respiratory system.

Aggravated Medical Conditions

None Known.

Principal Routes of Exposure

Eyes. Inhalation.

Potential health effects

Eyes Exposure to vapors will cause the following effects. Irritation. Swelling.

Skin Exposure to vapors will cause the following effects. Skin Irritation.

Inhalation Exposure to vapors will cause the following effects. Irritation of the nose or throat. Central nervous system effects. Drowsiness. Dizziness. Headaches. Fatigue. Nausea. Extreme overexposure may cause. Kidney damage. Lung damage. Liver damage. Cardiac abnormalities. Damage to blood. Misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.

Ingestion May be harmful if swallowed.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Acetone	67-64-1	10-30
Propane	74-98-6	10-30

N-Butane	106-97-8	7-13
Barium Sulfate	7727-43-7	5-10
Ethylene glycol monopropyl ether	2807-30-9	3-7
Methylisobutyl ketone	108-10-1	3-7
Methyl Propyl Ketone	107-87-9	1-5
Xylene (mix)	1330-20-7	1-5
Isobutyl acetate	110-19-0	1-5
Titanium dioxide	13463-67-7	1-5
PM Acetate	108-65-6	0.5-1.5

4. FIRST AID MEASURES

Eye contact Remove to fresh air. Rinse thoroughly with plenty of water, also under the eyelids. Seek medical attention if irritation persists.

Skin contact Wash area thoroughly with soap and water. Remove and wash contaminated clothing before re-use.

Ingestion Call a physician or Poison Control Center immediately.

Inhalation Move to fresh air. If symptoms persist, call a physician.

5. FIRE FIGHTING MEASURES

Flash point °C -19
Flash point °F -2
Method No information available

Autoignition temperature °C Product is not self-igniting
Autoignition temperature °F

Flammability Limits (% in Air)
Upper 10.9
Lower 1.7

Suitable extinguishing media

Carbon dioxide (CO₂). Water spray. Alcohol-resistant foam. Sand.

Special protective equipment for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Fire and Explosion Hazards

Aerosol containers may vent, rupture or burst when heated to temperatures above 120°F. Vapors may form explosive mixture in air between upper and lower explosive limits which can be ignited by many sources, such as pilot lights, open flames, electrical motors and switches.

Sensitivity to shock

No information available.

Sensitivity to static discharge

No information available.

6. ACCIDENTAL RELEASE MEASURES**Methods for cleaning up**

Personnel should wear appropriate protective equipment. Follow all precautions for handling. Please refer to appropriate sections of MSDS for additional information. Evacuate area of unprotected and unnecessary personnel. Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs. Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up with inert absorbent material. Dispose of absorbent in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE**Handling**

Do not spray on a naked flame or any other incandescent material. Do not smoke. Protect against electrostatic charges.

Storage

Small pressurized containers of flammable product may be stored in areas suitable for ordinary combustibles with respect to construction, drainage, control of ignition sources, and ventilation except that they should not be stored in basements. Keep away from heat. Keep away from direct sunlight. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	OSHA PEL (TWA)	OSHA PEL (Ceiling)	ACGIH OEL (TWA)	ACGIH OEL (STEL)
Acetone	1000 ppm 2400 mg/m ³	-	500 ppm	750 ppm
Propane	1000 ppm 1800 mg/m ³	-	1000 ppm	-
N-Butane	-	-	-	1000 ppm
Barium Sulfate	15 mg/m ³	-	10 mg/m ³	-
Ethylene glycol monopropyl ether	-	-	-	-
Methylisobutyl ketone	100 ppm 410 mg/m ³	-	20 ppm	75 ppm
Methyl Propyl Ketone	200 ppm 700 mg/m ³	-	-	150 ppm
Xylene (mix)	100 ppm 435 mg/m ³	-	100 ppm	150 ppm
Isobutyl acetate	150 ppm 700 mg/m ³	-	150 ppm	-
Titanium dioxide	15 mg/m ³	-	10 mg/m ³	-
PM Acetate	-	-	-	-

Ventilation and Environmental Controls

Adequate ventilation should be provided to keep exposure levels below current acceptable exposure limits.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product.

Respiratory protection

None necessary under normal conditions. Use NIOSH approved respirator if TLV limit is exceeded.

Hand Protection

Chemical resistant gloves. Consult glove manufacturer to determine the proper type for a specific operation.

Eye protection

Tightly fitting safety goggles.

Skin and body protection

None necessary under normal conditions

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Aerosol
Color	Blue
Odor	Solvent
Odor Threshold	No information available
pH	No data available
Specific Gravity	0.77-0.85
Vapor pressure	40 PSI @ 70 F
Density	0.83567 g/cm ³ @ 20°C (68°F)
Vapor density	No data available
Evaporation Rate	No data available
Water solubility	No data available
VOC Content	46.5%; 501.2 g/l; 4.18 lb/gal
Solids content	31.7%
MIR value	1.11
Partition Coefficient (n-octanol/water)	No data available
Boiling point/range °C	-44
Boiling point/range °F	-47
Melting point/range °C	No data available
Melting point/range °F	No data available
Flash point °C	-19
Flash point °F	-2
Ignition temperature °C	230
Ignition temperature °F	446

10. STABILITY AND REACTIVITY**Stability**

Stable under normal conditions.

Conditions to avoid

Do not store in temperatures above 120 degrees F.

Incompatibility

None known.

Hazardous Decomposition Products

None known.

Polymerization

Hazardous polymerization does not occur

11. TOXICOLOGICAL INFORMATION**Component Information**

Chemical Name	LD50 (oral, rat)	LD50 (dermal, rat/rabbit)	LC50 (inhalation, rat)
Acetone 67-64-1	-	-	50100 mg/m ³
Propane 74-98-6	-	-	658 mg/L
N-Butane 106-97-8	-	-	658 g/m ³
Barium Sulfate 7727-43-7	-	-	-
Ethylene glycol monopropyl ether 2807-30-9	-	870 mg/kg	1530 ppm
Methylisobutyl ketone 108-10-1	2080 mg/kg	16000 mg/kg	8.2 mg/L
Methyl Propyl Ketone 107-87-9	1600 mg/kg	-	-
Xylene (mix) 1330-20-7	4300 mg/kg	-	47635 mg/L
Isobutyl acetate 110-19-0	13400 mg/kg	17400 mg/kg	-
Titanium dioxide 13463-67-7	10000 mg/kg	-	-
PM Acetate 108-65-6	8532 mg/kg	5 g/kg	-

Synergistic Products None known**Potential health effects****Sensitization** None known**Chronic toxicity** None known**Mutagenic effects** None known**Teratogenic effects** None known**Reproductive toxicity** None known

Target Organ Effects Reports have associated prolonged overexposure to solvents with permanent brain and nervous system damage. Prolonged or repeated occupational overexposure may affect the following: Kidney. Lungs. Liver. Heart. Blood.

Carcinogenic effects

See table below

Chemical Name	ACGIH OEL - Carcinogens	IARC	NTP - Known Carcinogens	NTP - Suspected Human Carcinogens	OSHA RTK Carcinogens
Acetone	A4	Not Listed	Not Listed	Not Listed	Not Listed
Propane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
N-Butane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Barium Sulfate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Methylisobutyl ketone	A3	Group 2B	Not Listed	Not Listed	Listed
Methyl Propyl Ketone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Xylene (mix)	A4	Not Listed	Not Listed	Not Listed	Not Listed
Isobutyl acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Titanium dioxide	A4	Group 2B	Not Listed	Not Listed	Listed
PM Acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION**Acetone****Microtox Data***Photobacterium phosphoreum* EC50=14500 mg/L (15 min)**Water Flea Data***Daphnia magna* EC5010294 - 17704 mg/L (48 h)*Daphnia magna* EC5012600 - 12700 mg/L (48 h)**Methylisobutyl ketone****Microtox Data***Photobacterium phosphoreum* EC50=79.6 mg/L (5 min)**Water Flea Data***Daphnia magna* EC50=170 mg/L (48 h)**Xylene (mix)****Microtox Data***Photobacterium phosphoreum* EC50=0.0084 mg/L (24 h)**Water Flea Data***Gammarus lacustris* LC50=0.6 mg/L (48 h)*water flea* EC50=3.82 mg/L (48 h)**PM Acetate****Water Flea Data***Daphnia magna* EC50>500 mg/L (48 h)**13. DISPOSAL CONSIDERATIONS****Disposal Information**

Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate. Please recycle empty container whenever possible.

Product code **53395**

Product name **High Solids
Ford Tractor Blue Spray
Paint**

14. TRANSPORTATION INFORMATION

DOT

Consumer commodity, ORM-D.

TDG

UN1950 AEROSOLS, flammable, 2.1

15. REGULATORY INFORMATION

Chemical Name	US EPA SARA 313 Emission Reporting
Barium Sulfate	Listed
Ethylene glycol monopropyl ether	Listed
Methylisobutyl ketone	Listed
Xylene (mix)	Listed

State Regulations

Chemical Name	New Jersey - RTK	Pennsylvania - RTK	California Prop. 65
Acetone	Not Listed	Listed	Not Listed
Propane	Listed	Listed	Not Listed
N-Butane	Not Listed	Listed	Not Listed
Barium Sulfate	Not Listed	Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Not Listed	Not Listed
Methylisobutyl ketone	Listed	Listed	Carcinogen
Methyl Propyl Ketone	Not Listed	Listed	Not Listed
Xylene (mix)	Not Listed	Listed	Not Listed
Isobutyl acetate	Listed	Listed	Not Listed
Titanium dioxide	Not Listed	Listed	Carcinogen
PM Acetate	Not Listed	Not Listed	Not Listed

International Inventories

Chemical Name	EINECS	DSL	NDSL	TSCA
Acetone	X	X	-	X
Propane	X	X	-	X
N-Butane	X	X	-	X
Barium Sulfate	X	X	-	X
Ethylene glycol monopropyl ether	X	X	-	X
Methylisobutyl ketone	X	X	-	X
Methyl Propyl Ketone	X	X	-	X
Xylene (mix)	X	X	-	X
Isobutyl acetate	X	X	-	X
Titanium dioxide	X	X	-	X
PM Acetate	X	X	-	X

CPR

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by the Controlled Product Regulations

16. OTHER INFORMATION

NFPA

Health - 1
Flammability - 4
Reactivity - 3

HMIS

Health - 1
Flammability - 4
Physical Hazard - 3

Prepared By

V. Shargorodsky, Regulatory Affairs
Engineer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.